



GM Holden Ltd

Trading as Holden
191 Salmon Street Port Melbourne
Victoria 3207 Australia
ABN 84 006 893 232
All correspondence to:
GPO Box 1714 Melbourne
Victoria 3001 Australia
Telephone (03) 9647 1111
Facsimile (03) 9647 2550

4 September, 2013

National Manager Operations
Anti-Dumping Commission
5 Constitution Avenue
Canberra. ACT 2601

Email: clientsupport@adcommission.gov.au

Dear Sir / Madam

Application for Ministerial Exemption under Sections 8(7)(b) and 10(8)(aa) of the Customs Tariff (Anti-Dumping) Act re: Dumping measures applied to Zinc coated (Galvanised) steel exported from Peoples Republic of China, Korea and Taiwan (Report 190).

GM Holden currently imports certain Zinc coated (Galvanised) steel, the subject of measures following the above mentioned investigation.

Sections 8(7)(b) and (10)(8)(aa) of the Customs Tariff (Anti-Dumping) Act provide for exemptions from measures where goods are subject to Tariff Concession Orders pursuant to Part XVA of the Customs Act 1901.

GM Holden herewith formally applies for exemption from interim dumping duty and dumping duty of certain goods covered by Tariff Concessions as detailed below. This request is consistent with the directions provided by the Commission in its report to the Minister, Report 190 (paragraph 7.3.1.4), "In the event of future TCO's being granted, parties are able to make individual applications if and when they arise".

The Exemptions being sought are for certain goods covered by the following Tariff Concessions:

Tariff Item	TCO Number	Operative Date	Declared Date
7210.30.00	TC1316842	22/5/13	12/8/13
7210.49.00	TC1316841	22/5/13	12/8/13
7225.50.00	TC1316843	22/5/13	12/8/13
7225.92.00	TC1316844	22/5/13	12/8/13
7225.99.00	TC1316845	22/5/13	12/8/13

We enclose copies the said Tariff Concessions as published in the Commonwealth of Australia Gazette, Tariff Concessions No.TC13/32, Wednesday, 14 August, 2013.

We request that you consider this application and recommend that the Minister approves the exemption.

Sincerely

Alex Menta
Regional Customs Manager,
Australia & New Zealand



CUSTOMS ACT 1901 - NOTICE PURSUANT TO SECTION 269R(1) - TARIFF CONCESSION ORDERS MADE

Tariff Concession Orders have been made for the goods described in the following TABLE.

The operative date (Op.) and TC reference No. follow the description of goods. Local manufacturers of substitutable goods may request the revocation of TCOs at any time.

THE TABLE

Description of Goods including the Customs Tariff Classification	Schedule 4 Item Number Last Date of Effect
2836.20.00 DISODIUM CARBONATE Op. 16.05.13	Dec. date 09.08.13 - TC 1316114 50
6806.90.90 PANELS, REFRACTORY, vermiculite, magnesium aluminium iron silicate based, having ALL of the following: (a) magnesium oxide (MgO) content NOT less than 8.8%; (b) silica (SiO ₂) content NOT less than 46%; (c) service temperature NOT less than 1 100 degrees Celsius Op. 06.05.13	Dec. date 12.08.13 - TC 1314688 50
7210.30.00 STEEL, flat rolled, non-alloy, electrolytically plated OR coated with zinc, in coils, having ALL of the following: (a) yield strength NOT less than 110 MPa and NOT greater than 240 MPa; (b) tensile strength NOT less than 260 MPa; (c) elongation NOT less than 37%; (d) coating mass NOT less than 36 g/m ² and NOT greater than 90 g/m ² on each side; (e) in ANY of the following sizes: (i) thickness 0.70 mm and width 980 mm; (ii) thickness 0.70 mm and width 1 160 mm; (iii) thickness 0.70 mm and width 1 250 mm; (iv) thickness 0.70 mm and width 1 520 mm; (v) thickness 0.70 mm and width 1 640 mm; (vi) thickness 0.80 mm and width 960 mm; (vii) thickness 0.80 mm and width 1 160 mm; (viii) thickness 0.80 mm and width 1 370 mm; (ix) thickness 0.80 mm and width 1 600 mm; (x) thickness 0.90 mm and width 950 mm	50
For the purposes of this Order, tolerances allowable for specification (e) are: (a) thickness +/- 10% (b) width +/- 1% Op. 22.05.13	Dec. date 12.08.13 - TC 1316842
7210.49.00 STEEL, flat rolled, non-alloy, hot dipped zinc coated, in coils, having ALL of the following: (a) yield strength NOT less than 110 MPa and NOT greater than 280 MPa; (b) tensile strength NOT less than 260 MPa; (c) elongation NOT less than 37%; (d) coating mass NOT less than 45 g/m ² and NOT greater than 100 g/m ² on each side; (e) in ANY of the following sizes: (i) thickness 0.60 mm and width 1 670 mm; (ii) thickness 0.65 mm and width 960 mm; (iii) thickness 0.65 mm and width 1 075 mm; (iv) thickness 0.65 mm and width 1 160 mm; (v) thickness 0.65 mm and width 1 240 mm; (vi) thickness 0.65 mm and width 1 425 mm; (vii) thickness 0.65 mm and width 1 430 mm; (viii) thickness 0.65 mm and width 1 445 mm;	50

(Continued on next page)

Description of Goods including the
Customs Tariff ClassificationSchedule 4 Item Number
Last Date of Effect

(Continued from previous page)

- (ix) thickness 0.65 mm and width 1 630 mm;
- (x) thickness 0.65 mm and width 1 730 mm;
- (xi) thickness 0.70 mm and width 810 mm;
- (xii) thickness 0.70 mm and width 840 mm;
- (xiii) thickness 0.70 mm and width 850 mm;
- (xiv) thickness 0.70 mm and width 890 mm;
- (xv) thickness 0.70 mm and width 896 mm;
- (xvi) thickness 0.70 mm and width 1 390 mm;
- (xvii) thickness 0.70 mm and width 1 400 mm;
- (xviii) thickness 0.70 mm and width 1 410 mm;
- (xix) thickness 0.70 mm and width 1 440 mm;
- (xx) thickness 0.70 mm and width 1 460 mm;
- (xxi) thickness 0.70 mm and width 1 540 mm;
- (xxii) thickness 0.70 mm and width 1 590 mm;
- (xxiii) thickness 0.70 mm and width 1 650 mm;
- (xxiv) thickness 0.70 mm and width 1 655 mm;
- (xxv) thickness 0.75 mm and width 1 600 mm;
- (xxvi) thickness 0.75 mm and width 1 695 mm;
- (xxvii) thickness 0.75 mm and width 1 760 mm;
- (xxviii) thickness 0.80 mm and width 680 mm;
- (xxix) thickness 0.80 mm and width 1 185 mm;
- (xxx) thickness 0.80 mm and width 1 300 mm;
- (xxxi) thickness 0.80 mm and width 1 370 mm;
- (xxxii) thickness 0.80 mm and width 1 325 mm;
- (xxxiii) thickness 0.80 mm and width 1 545 mm;
- (xxxiv) thickness 0.80 mm and width 1 600 mm;
- (xxxv) thickness 0.80 mm and width 1 695 mm;
- (xxxvi) thickness 0.80 mm and width 1 760 mm;
- (xxxvii) thickness 0.80 mm and width 1 840 mm;
- (xxxviii) thickness 0.90 mm and width 950 mm;
- (xxxix) thickness 0.90 mm and width 1 530 mm;
- (xl) thickness 0.90 mm and width 1 800 mm;
- (xli) thickness 1.20 mm and width 1 730 mm;
- (xlii) thickness 1.20 mm and width 1 770 mm

For the purposes of this Order, tolerances allowable for specification (e) are:

(a) thickness +/- 10%

(b) width +/- 1%

Op. 22.05.13

Dec. date 12.08.13

TC 1316841

7225.50.00

STEEL, flat rolled, alloy, cold rolled, in coils, having ALL
of the following:

50

- (a) yield strength NOT less than 340 MPa and NOT greater than 900 MPa;
- (b) tensile strength NOT less than 590 MPa;
- (c) total elongation NOT less than 8%;
- (d) in ANY of the following sizes:
 - (i) thickness 1.20 mm and width 820 mm;
 - (ii) thickness 1.20 mm and width 1 180 mm;
 - (iii) thickness 1.20 mm and width 1 250 mm

For the purposes of this Order, tolerances allowable for specification (d) are:

(a) thickness +/- 10%

(b) width +/- 1%

Op. 22.05.13

Dec. date 12.08.13

TC 1316843

Description of Goods including the Customs Tariff Classification Schedule 4 Item Number
Last Date of Effect

7225.92.00 STEEL, flat rolled, alloy, hot dipped zinc coated, in coils, having ALL of the following: 50

- (a) yield strength NOT less than 340 MPa and NOT greater than 700 MPa;
- (b) tensile strength NOT less than 590 MPa;
- (c) elongation NOT less than 10%;
- (d) coating mass NOT less than 60 g/m² and NOT greater than 120 g/m² on each side;
- (e) in ANY of the following sizes:
 - (i) thickness 1.20 mm and width 615 mm;
 - (ii) thickness 1.20 mm and width 623 mm;
 - (iii) thickness 1.20 mm and width 1 115 mm;
 - (iv) thickness 1.20 mm and width 1 240 mm;
 - (v) thickness 1.20 mm and width 1 256 mm;
 - (vi) thickness 1.40 mm and width 900 mm;
 - (vii) thickness 1.80 mm and width 970 mm;
 - (viii) thickness 2.00 mm and width 889 mm;
 - (ix) thickness 2.00 mm and width 970 mm;
 - (x) thickness 2.00 mm and width 992 mm

For the purposes of this Order, tolerances allowable for specification (e) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

Op. 22.05.13

Dec. date 12.08.13

- TC 1316844 ✓

7225.99.00 STEEL, flat rolled, alloy, in coils, having ALL of the following: 50

- (a) hot dipped coating having BOTH of the following:
 - (i) NOT less than 85% aluminium;
 - (ii) NOT less than 5% silicon and NOT greater than 11% silicon;
- (b) coating mass NOT less than 60 g/m² and NOT greater than 100 g/m² on each side;
- (c) yield strength NOT less than 300 MPa;
- (d) tensile strength NOT less than 500 MPa;
- (e) elongation NOT less than 17%;
- (f) in ANY of the following sizes:
 - (i) thickness 1.00 mm and width 938 mm;
 - (ii) thickness 1.20 mm and width 1 202 mm;
 - (iii) thickness 1.40 mm and width 918 mm;
 - (iv) thickness 1.40 mm and width 995 mm;
 - (v) thickness 2.00 mm and width 1 325 mm

For the purposes of this order, tolerances allowable for specification (f) are:

- (a) thickness +/- 10%;
- (b) width +/- 1%

Op. 22.05.13

Dec. date 12.08.13

- TC 1316845 ✓

7326.90.90 CONNECTORS, SUBSEA CONTROL MODULE, being hub AND receiver 50

Op. 23.05.13

Dec. date 12.08.13

- TC 1316881

8307.10.00 TUBES, SOLAR WATER HEATING, corrugated, welded stainless steel, having BOTH of the following: 50

- (a) rubber insulation sheath;
- (b) two core sensor cable

Op. 23.05.13

Dec. date 12.08.13

- TC 1316847

8309.90.00 ENDS, CAN, tin plate OR tin free steel, lacquered, non ring pull, having diameters of 62 mm OR 96 mm 50

For the purposes of this order, diameters referenced have tolerances of + or - 1 mm

Op. 17.05.13

Dec. date 12.08.13

- TC 1316288

8419.50.90 HEAT EXCHANGERS, SHELL AND TUBE, HOT OIL 50

Op. 22.05.13

Dec. date 12.08.13

- TC 1316779