

COMMONWEALTH OF AUSTRALIA

Ministerial Exemption Instrument No. 3 of 2013

Customs Tariff (Anti-Dumping) Act 1975

I, IAN MACFARLANE, Minister for Industry, under subsection 8(7) of the *Customs Tariff (Anti-Dumping) Act 1975*, hereby exempt the goods described in Attachment 1 (the Goods) from:

- interim dumping duty, and
- dumping duty,

as I am satisfied that a Tariff Concession Order under Part XVA of the *Customs Act 1901* in respect of the good is in force.

This instrument commences on the 14th day of March 2013.

Dated this 19th day of November 2013

IAN MACFARLANE
Minister for Industry

Attachment 1

CURRENT Tariff Concession Orders (TCO) for tariff classification 7208.27.00

All goods meeting at least one of the descriptions detailed below for the current TCOs are eligible for an exemption from dumping duties under Ministerial Exemption Instrument No. 3 of 2013.

TC 1309208

STEEL, flat rolled, iron OR non-alloy, hot rolled, pickled, not coated, in coils, complying with Japanese Industrial Standard G3131 (JIS G3131), grades SPHC OR SPHD OR SPHE, having ALL of the following:

- (a) tensile strength NOT less than 270 MPa;
- (b) total elongation NOT less than 27%;
- (c) in ANY of the following sizes:
 - (i) thickness 1.20 mm and width 610 mm;
 - (ii) thickness 1.20 mm and width 820 mm;
 - (iii) thickness 1.20 mm and width 838 mm;
 - (iv) thickness 1.40 mm and width 690 mm;
 - (v) thickness 1.40 mm and width 1 050 mm;
 - (vi) thickness 1.40 mm and width 1 080 mm;
 - (vii) thickness 1.40 mm and width 1 150 mm;
 - (viii) thickness 1.40 mm and width 1 390 mm;
 - (ix) thickness 1.60 mm and width 1 010 mm;
 - (x) thickness 1.90 mm and width 1 110 mm;
 - (xi) thickness 1.90 mm and width 1 340 mm;
 - (xii) thickness 1.90 mm and width 1 360 mm

For the purposes of this Order, tolerances allowable for specification (d) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

TC 1309209

STEEL, flat rolled, iron OR non-alloy, hot rolled, pickled, not coated, in coils, complying with Japanese Industrial Standard G3113 (JIS G3113), grades SAPH400 OR SAPH440, having ALL of the following:

- (a) yield strength NOT less than 255 MPa;
- (b) tensile strength NOT less than 400 MPa;
- (c) total elongation NOT less than 29%;
- (d) in ANY of the following sizes:
 - (i) thickness 1.40 mm and width 605 mm;
 - (ii) thickness 1.40 mm and width 1 053 mm;
 - (iii) thickness 1.40 mm and width 1 175 mm;
 - (iv) thickness 1.55 mm and width 1 115 mm;
 - (v) thickness 1.55 mm and width 1 150 mm;
 - (vi) thickness 1.60 mm and width 610 mm;
 - (vii) thickness 1.60 mm and width 1 027 mm;
 - (viii) thickness 1.60 mm and width 1 090 mm;

- (ix) thickness 1.60 mm and width 1 130 mm;
- (x) thickness 1.60 mm and width 1 150 mm;
- (xi) thickness 1.60 mm and width 1 270 mm;
- (xii) thickness 1.60 mm and width 1 315 mm;
- (xiii) thickness 1.60 mm and width 1 340 mm;
- (xiv) thickness 1.60 mm and width 1 380 mm;
- (xv) thickness 1.60 mm and width 1 430 mm;
- (xvi) thickness 1.60 mm and width 1 470 mm;
- (xvii) thickness 1.80 mm and width 600 mm;
- (xviii) thickness 1.80 mm and width 1 475 mm;
- (xix) thickness 1.95 mm and width 1 290 mm;
- (xx) thickness 2.00 mm and width 1 310 mm;
- (xxi) thickness 2.00 mm and width 1 440 mm;
- (xxii) thickness 2.00 mm and width 1 480 mm;
- (xxiii) thickness 2.00 mm and width 1 512 mm;
- (xxiv) thickness 2.20 mm and width 1 330 mm

For the purposes of this Order, tolerances allowable for specification (d) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

TC 1309212

STEEL, flat rolled, iron OR non-alloy, hot rolled, pickled, not coated, in coils, having ALL of the following:

- (a) yield strength NOT less than 305 MPa;
- (b) tensile strength NOT less than 490 MPa;
- (c) total elongation NOT less than 21%;
- (d) in ANY of the following sizes:
 - (i) thickness 1.60 mm and width 1 150 mm;
 - (ii) thickness 1.60 mm and width 1 230 mm;
 - (iii) thickness 1.90 mm and width 780 mm

For the purposes of this Order, tolerances allowable for specification (d) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

CURRENT Tariff Concession Orders (TCO) for tariff classification 7211.19.00

All goods meeting at least one of the descriptions detailed below for the current TCOs are eligible for an exemption from dumping duties under Ministerial Exemption Instrument No. 3 of 2013.

TC 1309210

STEEL, flat rolled, iron OR non-alloy, hot rolled, pickled, not coated, in coils, complying with Japanese Industrial Standard G3113 (JIS G3113), grades SAPH400 OR SAPH440, having ALL of the following:

- (a) yield strength NOT less than 255 MPa;
- (b) tensile strength NOT less than 400 MPa;
- (c) total elongation NOT less than 29%;

- (d) in ANY of the following sizes:
- (i) thickness 1.40 mm and width 585 mm;
 - (ii) thickness 1.55 mm and width 250 mm;
 - (iii) thickness 1.60 mm and width 360 mm;
 - (iv) thickness 1.60 mm and width 510 mm

For the purposes of this Order, tolerances allowable for specification (d) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

TC 1309213

STEEL, flat rolled, iron OR non-alloy, hot rolled, pickled, not coated, in coils, having ALL of the following:

- (a) yield strength NOT less than 305 MPa;
- (b) tensile strength NOT less than 490 MPa;
- (c) total elongation NOT less than 21%;
- (d) thickness 1.90 mm and width 423 mm

For the purposes of this Order, tolerances allowable for specification (d) are:

- (a) thickness +/- 10%
- (b) width +/- 1%