

**Confidential**

Ms Lydia Cooke  
Manager, Operations 1 International Trade  
Remedies Branch  
Australian Customs and Border Protection  
Service  
5 Constitution Avenue  
CANBERRA ACT 2616

12 March 2013

Our ref 11276/15955/80133959

Dear Ms Cooke

**Application for Ministerial Exemption under section 8(7) of the Customs Tariff (Anti-Dumping) Act 1975 (the Act)****Applicant: Nippon Steel & Sumitomo Metal Corporation**

We refer to the application for Ministerial Exemption from anti-dumping measures imposed on hot rolled coil steel (**HRC**) made by our client, Nippon Steel & Sumitomo Metal Corporation (**Nippon Steel**) dated 30 January 2012.

In its application, Nippon Steel sought, pursuant to section 8(7)(a) of the *Customs Tariff (Anti-Dumping) Act 1975 (Anti-Dumping Act)*, an exemption from dumping duties for '*pickled and oiled HRC exported from Japan*' on the basis that like or directly competitive goods are not offered for sale in Australia to all purchasers on equal terms under like conditions having regard to the custom and usage of trade.

We note that section 8(7)(b) of the Anti-Dumping Act provides another basis for the Minister to exempt goods from dumping duties - that is, if he is satisfied that a Tariff Concession Order under Part XVA of the *Custom Act 1901 (Customs Act)* is in force in respect of goods which are the subject of dumping duties.

BlueScope has applied for a Tariff Concession Order under Part XVA of the Customs Act in respect of some of the goods which were the subject of its anti-dumping application and to which dumping duties now apply. The details of BlueScope's Tariff Concession Order application appear in the Commonwealth of Australia Gazette TC 13/10 of 23 January 2013 (**Commonwealth Gazette**) at pages 3-12.

BlueScope's Tariff Concession Order application is made in respect of certain categories of product which are also the subject of Nippon Steel's Ministerial Exemption application. More particularly, BlueScope has indicated the "*Stated Use*" of these categories of goods (as set out in the Commonwealth

Ms Lydia Cooke, Australian Customs and Border Protection Service

12 March 2013

Gazette) as "In PMV [Passenger Motor Vehicles]". Industry

BlueScope's Tariff Concession Order application is based on the ground that on the day on which the application was lodged, no substitutable goods in relation to the goods the subject of the Tariff Concession Order application were produced in Australia in the ordinary course of business (see discussion of core criteria for a Tariff Concession Order in *Australian Customs Service Manual, "Tariff Concessions", Vol 13 (Manual)*).

We submit that BlueScope's Tariff Concession Order application is an admission by it that the goods, or like or directly competitive goods, which are the subject of its Tariff Concession Order, are not offered for sale in Australia to all purchasers on equal terms under like conditions having regard to the custom and usage of trade. The relevant goods fall within the following Customs Tariff Classifications:

- 7208.26.00;
- 7208.27.00;
- 7209.16.00;
- 7209.17.00;
- 7209.18.00;
- 7210.30.00;
- 7210.49.00; and
- 7226.92.00.

Attached to this letter is an excerpt of the Commonwealth Gazette which lists each of the Customs Tariff Classifications referred to above together with the particular grounds for exemption being sought based on the precise description of product contained in that description of goods.

We note that of the goods that are the subject of BlueScope's Tariff Concession Order application, goods falling within Customs Tariff Classification 7208.26.00 and 7208.27.00 are the subject of dumping duties.<sup>1</sup>

BlueScope's grounds for the making of a Tariff Concession Order in respect of goods falling within the Customs Tariff Classification 7208.26.00 and 7208.27.00 includes specific references to pickled HRC steel. This is the product Industry the subject of its Ministerial Exemption application.

We submit that, in applying for a Tariff Concession Order over the relevant goods (and in particular, goods falling within Customs Tariff Classification 7208.26.00 and 7208.27.00), BlueScope has conceded that, in respect of those goods, like or directly competitive goods are not offered for sale in Australia to all purchasers on equal terms under like conditions having regard to the custom and usage of trade.

---

<sup>1</sup> Decision of the Minister for Home Affairs dated 4 December 2012 following consideration of International Trade Remedies Report No.188.

Ms Lydia Cooke, Australian Customs and Border Protection Service

12 March 2013

We consider that the matters set out above further supports Nippon Steel's claim for Ministerial Exemption from dumping duties for the goods the subject of its Ministerial Exemption application dated 30 January 2013.

Yours sincerely



**Zac Chami, Partner**  
+61 2 9353 4744  
zchami@claytonutz.com

**Michael Mulgrew, Consultant**  
+61 2 9353 3054  
mmulgrew@claytonutz.com





**Commonwealth  
of Australia**

# Gazette

**No. TC 13/03, Wednesday, 23 January 2013**  
Published by the Commonwealth of Australia

**TARIFF CONCESSIONS**

## CONTENTS

TCO Applications .....	2
TCO Applications Reworded .....	16
TCO Applications Refused .....	17
TCOs Made .....	18
Local Manufacturer Initiated - TCO Revocation Requests .....	19
Local Manufacturer Initiated - TCOs Revoked .....	20
TCOs Revoked Unused for Over 2 years .....	21
TCOs Intention to Revoke - Unused for Over 2 years .....	22
Section 273 Determinations Made .....	26
Amended notification AAT Review of TCO Applications Results .....	27

The Australian Customs and Border Protection Service (Customs and Border Protection) publishes the Commonwealth of Australia Tariff Concessions Gazette (the Tariff Concessions Gazette) free of charge on the Customs internet site at: <http://www.customs.gov.au>

Please select "tariff", then "tariff concessions gazette".

The gazettes are listed in date order and may be selected from the list of Adobe (PDF) files.

General Inquiries: .....	(02) 6275 6404
Facsimile: .....	(02) 6275 6376

## 3 TCO Applications

Commonwealth of Australia Gazette  
No TC 13/03, Wednesday, 23 Jan 2013Description of Goods including the  
Customs Tariff ClassificationSchedule 4 Item Number  
General Duty Rate

7208.26.00 STEEL, flat rolled, iron OR non-alloy steel, hot rolled, 50

pickled, not coated, in coils, complying with Japanese  
Industrial Standard G3134 (JIS G3134) grade SPFH590 OR Japanese  
Industrial Standard G3113 (JIS G3113) grade SAPH440, having ALL  
of the following:

- (a) yield strength NOT less than 265 MPa and NOT greater than 600 MPa;
- (b) tensile strength NOT less than 440 MPa;
- (c) total elongation NOT less than 18% and NOT greater than 46%;
- (d) in EITHER of the following sizes:
  - (i) thickness 3.20 mm and width 1 034 mm;
  - (ii) thickness 3.20 mm and width 1 350 mm

For the purposes of this Order, tolerances allowable for  
specification (d) are:

- (a) thickness +/- 10%
  - (b) width +/- 1%
- Op. 28.12.12

- TC 1349335

Stated Use:

In PMV car body outer skins

Applicant: BLUESCOPE STEEL (AIS) PTY LTD

5%

7208.27.00 STEEL, flat rolled, iron OR non-alloy steel, hot rolled, 50

pickled, not coated, in coils, complying with Japanese  
Industrial Standard G3131 (JIS G3131), grades SPHC OR SPHD,  
having ALL of the following:

- (a) yield strength NOT less than 175 MPa and NOT greater than 325 MPa;
- (b) tensile strength NOT less than 270 MPa;
- (c) total elongation NOT less than 35% and NOT greater than 53%;
- (d) in ANY of the following sizes:
  - (i) thickness 1.40 mm and width 1 050 mm;
  - (ii) thickness 1.40 mm and width 1 330 mm;
  - (iii) thickness 1.60 mm and width 1 228 mm;
  - (iv) thickness 1.80 mm and width 1 025 mm

For the purposes of this Order, tolerances allowable for  
specification (d) are:

- (a) thickness +/- 10%
  - (b) width +/- 1%
- Op. 28.12.12

- TC 1349331

Stated Use:

In PMV car body outer skins

Applicant: BLUESCOPE STEEL (AIS) PTY LTD

5%



## 4 TCO Applications

Commonwealth of Australia Gazette  
No TC 13/03, Wednesday, 23 Jan 2013

Description of Goods including the Customs Tariff Classification	Schedule 4 Item Number General Duty Rate
<p>7208.27.00 STEEL, flat rolled, iron OR non-alloy steel, hot rolled, pickled, not coated, in coils, complying with Japanese Industrial Standard G3134 (JIS G3134) grade SPFH590 OR Japanese Industrial Standard G3113 (JIS G3133) grade SAPH440, having ALL of the following:</p> <ul style="list-style-type: none"> <li>(a) yield strength NOT less than 265 MPa and NOT greater than 600 MPa;</li> <li>(b) tensile strength NOT less than 440 MPa;</li> <li>(c) total elongation NOT less than 18% and NOT greater than 46%;</li> <li>(d) in ANY of the following sizes: <ul style="list-style-type: none"> <li>(i) thickness 1.40 mm and width 1 150 mm;</li> <li>(ii) thickness 2.00 mm and width 836 mm;</li> <li>(iii) thickness 2.60 mm and width 1 120 mm;</li> <li>(iv) thickness 2.60 mm and width 1 246 mm</li> </ul> </li> </ul> <p>For the purposes of this Order, tolerances allowable for specification (d) are:</p> <ul style="list-style-type: none"> <li>(a) thickness +/- 10%</li> <li>(b) width +/- 1%</li> </ul> <p>Op. 28.12.12</p> <p>Stated Use: In PMV car body outer skins</p> <p>Applicant: BLUESCOPE STEEL (AIS) PTY LTD</p>	50
<p>7209.16.00 STEEL, flat rolled, iron OR non-alloy steel, cold rolled, in coils, not coated, complying with Japanese Industrial Standard G3135 (JIS G3135), grade SPFC440 OR SPFC590, having ALL of the following:</p> <ul style="list-style-type: none"> <li>(a) yield strength NOT less than 265 MPa and NOT greater than 560 MPa;</li> <li>(b) tensile strength NOT less than 440 MPa;</li> <li>(c) total elongation NOT less than 18%;</li> <li>(d) in ANY of the following sizes: <ul style="list-style-type: none"> <li>(i) thickness 1.20 mm and width 962 mm;</li> <li>(ii) thickness 1.20 mm and width 1 090 mm;</li> <li>(iii) thickness 1.20 mm and width 1 306 mm;</li> <li>(iv) thickness 1.40 mm and width 715 mm;</li> <li>(v) thickness 1.40 mm and width 1 182 mm;</li> <li>(vi) thickness 1.40 mm and width 1 185 mm;</li> <li>(vii) thickness 1.40 mm and width 1 302 mm;</li> <li>(viii) thickness 1.60 mm and width 1 240 mm;</li> <li>(ix) thickness 1.80 mm and width 1 132 mm;</li> <li>(x) thickness 1.80 mm and width 1 166 mm;</li> <li>(xi) thickness 1.80 mm and width 1 225 mm;</li> <li>(xii) thickness 2.00 mm and width 890 mm;</li> <li>(xiii) thickness 2.00 mm and width 990 mm</li> </ul> </li> </ul> <p>For the purposes of this Order, tolerances allowable for specification (d) are:</p> <ul style="list-style-type: none"> <li>(a) thickness +/- 10%</li> <li>(b) width +/- 1%</li> </ul> <p>Op. 28.12.12</p> <p>Stated Use: In PMV car body outer skins</p> <p>Applicant: BLUESCOPE STEEL (AIS) PTY LTD</p>	50

- TC 1349332

- TC 1349343

5%

## 5 TCO Applications

Commonwealth of Australia Gazette  
No TC 13/03, Wednesday, 23 Jan 2013Description of Goods including the  
Customs Tariff ClassificationSchedule 4 Item Number  
General Duty Rate

7209.17.00	<p>STEEL, flat rolled, iron OR non-alloy steel, cold rolled, not coated, in coils, having ALL of the following;</p> <p>(a) yield strength NOT greater than 210 MPa;</p> <p>(b) tensile strength NOT less than 250 MPa;</p> <p>(c) total elongation NOT less than 40%;</p> <p>(d) in ANY of the following sizes:</p> <p>(i) thickness 0.75 mm and width 1 150 mm;</p> <p>(ii) thickness 0.75 mm and width 1 435 mm;</p> <p>(iii) thickness 0.75 mm and width 1 565 mm;</p> <p>(iv) thickness 0.75 mm and width 1 640 mm;</p> <p>(v) thickness 0.75 mm and width 1 700 mm;</p> <p>(vi) thickness 0.80 mm and width 1 220 mm;</p> <p>(vii) thickness 0.80 mm and width 1 565 mm;</p> <p>(viii) thickness 0.80 mm and width 1 580 mm;</p> <p>(ix) thickness 0.80 mm and width 1 584 mm;</p> <p>(x) thickness 0.80 mm and width 1 585 mm;</p> <p>(xi) thickness 0.80 mm and width 1 590 mm;</p> <p>(xii) thickness 0.80 mm and width 1 625 mm;</p> <p>(xiii) thickness 0.85 mm and width 1 730 mm</p> <p>For the purposes of this Order, tolerances allowable for specification (d) are:</p> <p>(a) thickness +/- 10%</p> <p>(b) width +/- 1%</p> <p>Op. 24.12.12</p>	50
------------	--	----

- TC 1248927

Stated Use:  
In PMV car body outer skins

Applicant: BLUESCOPE STEEL (AIS) PTY LTD

5%

7209.17.00	<p>STEEL, flat rolled, iron OR non-alloy steel, cold rolled, not coated, in coils, having ALL of the following:</p> <p>(a) yield strength NOT less than 185 MPa;</p> <p>(b) tensile strength NOT less than 340 MPa;</p> <p>(c) total elongation NOT less than 32%;</p> <p>(d) in ANY of the following sizes:</p> <p>(i) thickness 0.70 mm and width 1 235 mm;</p> <p>(ii) thickness 0.70 mm and width 1 350 mm;</p> <p>(iii) thickness 0.70 mm and width 1 425 mm;</p> <p>(iv) thickness 0.70 mm and width 1 450 mm;</p> <p>(v) thickness 0.70 mm and width 1 453 mm;</p> <p>(vi) thickness 0.70 mm and width 1 470 mm;</p> <p>(vii) thickness 0.70 mm and width 1 485 mm;</p> <p>(viii) thickness 0.70 mm and width 1 510 mm;</p> <p>(ix) thickness 0.70 mm and width 1 520 mm;</p> <p>(x) thickness 0.70 mm and width 1 530 mm;</p> <p>(xi) thickness 0.75 mm and width 1 390 mm;</p> <p>(xii) thickness 0.75 mm and width 1 525 mm;</p> <p>(xiii) thickness 0.75 mm and width 1 555 mm;</p> <p>(xiv) thickness 0.75 mm and width 1 710 mm;</p> <p>(xv) thickness 0.75 mm and width 1 740 mm;</p> <p>(xvi) thickness 0.75 mm and width 1 800 mm;</p> <p>(xvii) thickness 0.80 mm and width 1 435 mm;</p> <p>(xviii) thickness 0.80 mm and width 1 585 mm</p> <p>For the purposes of this Order, tolerances allowable for specification (d) are:</p> <p>(a) thickness +/- 10%</p> <p>(b) width +/- 1%</p> <p>Op. 24.12.12</p>	50
------------	--	----

- TC 1248928

Stated Use:  
In PMV car body outer skins

Applicant: BLUESCOPE STEEL (AIS) PTY LTD

5%

## 6 TCO Applications

Commonwealth of Australia Gazette  
No TC 13/03, Wednesday, 23 Jan 2013

Description of Goods including the Customs Tariff Classification	Schedule 4 Item Number General Duty Rate
<p>7209.17.00 STEEL, flat rolled, iron OR non-alloy steel, cold rolled, not coated, in coils, complying with Japanese Industrial Standard G3141 (JIS G3141) grades SPCC, SPCCD OR SPCE having ALL of the following:</p> <ul style="list-style-type: none"> <li>(a) yield strength NOT less than 115 MPa and NOT greater than 265 MPa;</li> <li>(b) tensile strength NOT less than 270 MPa;</li> <li>(c) total elongation NOT less than 36% and NOT greater than 57%;</li> <li>(d) in ANY of the following sizes: <ul style="list-style-type: none"> <li>(i) thickness 0.50 mm and width 870 mm;</li> <li>(ii) thickness 0.55 mm and width 1 430 mm;</li> <li>(iii) thickness 0.75 mm and width 1 625 mm;</li> <li>(iv) thickness 0.75 mm and width 1 670 mm</li> </ul> </li> </ul> <p>For the purposes of this Order, tolerances allowable for specification (d) are:</p> <ul style="list-style-type: none"> <li>(a) thickness +/- 10%</li> <li>(b) width +/- 1%</li> </ul> <p>Op. 28.12.12</p>	50
<p>Stated Use: For use in PMV car body outer skins</p> <p>Applicant: BLUESCOPE STEEL (AIS) PTY LTD</p>	5%
<p>7209.17.00 STEEL, flat rolled, iron OR non-alloy steel, cold rolled, not coated, in coils, complying with Japanese Industrial Standard G3135 (JIS G3135), grades SPFC440, OR SPFC590, having ALL of the following:</p> <ul style="list-style-type: none"> <li>(a) yield strength NOT less than 265 MPa and NOT greater than 560 MPa;</li> <li>(b) tensile strength NOT less than 440 MPa;</li> <li>(c) total elongation NOT less than 18%;</li> <li>(d) in ANY of the following sizes: <ul style="list-style-type: none"> <li>(i) thickness 0.80 mm and width 1 097 mm;</li> <li>(ii) thickness 1.00 mm and width 1 010 mm;</li> <li>(iii) thickness 1.00 mm and width 1 120 mm;</li> <li>(iv) thickness 1.00 mm and width 1 390 mm</li> </ul> </li> </ul> <p>For the purposes of this Order, tolerances allowable for specification (d) are:</p> <ul style="list-style-type: none"> <li>(a) thickness +/- 10%</li> <li>(b) width +/- 1%</li> </ul> <p>Op. 28.12.12</p>	50
<p>Stated Use: In PMV car body outer skins</p> <p>Applicant: BLUESCOPE STEEL (AIS) PTY LTD</p>	5%

- TC 1349338

- TC 1349341



## 7 TCO Applications

Commonwealth of Australia Gazette  
No TC 13/03, Wednesday, 23 Jan 2013Description of Goods including the  
Customs Tariff ClassificationSchedule 4 Item Number  
General Duty Rate

7209.18.00	<p>STEEL, flat rolled, iron OR non-alloy steel, cold rolled, not coated, in coils, complying with Japanese Industrial Standard G3141 (JIS G3141) grades SPCC, SPCC OR SPCE, having ALL of the following:</p> <ul style="list-style-type: none"> <li>(a) yield strength NOT less than 115 MPa and NOT greater than 265 MPa;</li> <li>(b) tensile strength NOT less than 270 MPa;</li> <li>(c) total elongation NOT less than 36% and NOT greater than 57%;</li> <li>(d) in EITHER of the following sizes: <ul style="list-style-type: none"> <li>(i) thickness 0.40 mm and width 745 mm;</li> <li>(ii) thickness 0.40 mm and width 960 mm</li> </ul> </li> </ul> <p>For the purposes of this Order, tolerances allowable for specification (d) are:</p> <ul style="list-style-type: none"> <li>(a) thickness +/- 10%</li> <li>(b) width +/- 1%</li> </ul> <p>Op. 28.12.12</p> <p>Stated Use: In PMV car body outer skins</p> <p>Applicant: BLUESCOPE STEEL (AIS) PTY LTD</p>	50
	- TC 1349336	
7210.30.00	<p>STEEL, flat rolled, iron OR non-alloy steel, tin AND zinc alloy electrolytically coated, in coils, having ALL of the following:</p> <ul style="list-style-type: none"> <li>(a) yield strength NOT less than 115 MPa and NOT greater than 370 MPa;</li> <li>(b) tensile strength NOT less than 270 MPa;</li> <li>(c) total elongation NOT less than 33%;</li> <li>(d) total coating mass NOT less than 30 g/m2 and NOT greater than 50 g/m2 on each side;</li> <li>(e) thickness 0.40 mm and width 970 mm</li> </ul> <p>For the purposes of this Order, tolerances allowable for specification (e) are:</p> <ul style="list-style-type: none"> <li>(a) thickness +/- 10%</li> <li>(b) width +/- 1%</li> </ul> <p>Op. 28.12.12</p> <p>Stated Use: For use in PMV car body outer skins</p> <p>Applicant: BLUESCOPE STEEL (AIS) PTY LTD</p>	50
	- TC 1349355	
		5%

## 8 TCO Applications

Commonwealth of Australia Gazette  
No TC 13/03, Wednesday, 23 Jan 2013Description of Goods including the  
Customs Tariff ClassificationSchedule 4 Item Number  
General Duty Rate

7210.30.00 STEEL, flat rolled, iron OR non-alloy steel, tin AND zinc alloy electrolytically coated, in coils, having ALL of the following:

- (a) yield strength NOT less than 115 MPa and NOT greater than 370 MPa;
- (b) tensile strength NOT less than 270 MPa;
- (c) total elongation NOT less than 33%;
- (d) total coating mass NOT less than 30 g/m2 and NOT greater than 50 g/m2 on each side;
- (e) in ANY of the following sizes:
  - (i) thickness 0.60 mm and width 980 mm;
  - (ii) thickness 0.80 mm and width 1 159 mm;
  - (iii) thickness 0.80 mm and width 1 209 mm;
  - (iv) thickness 0.80 mm and width 890 mm;
  - (v) thickness 1.00 mm and width 780 mm;
  - (vi) thickness 1.00 mm and width 840 mm;
  - (vii) thickness 1.00 mm and width 865 mm

50

For the purposes of this Order, tolerances allowable for specification (e) are:

(a) thickness +/- 10%  
 (b) width +/- 1%  
 Op. 28.12.12

- TC 1349357

Stated Use:  
 In PMV car body outer skins

Applicant: BLUESCOPE STEEL (AIS) PTY LTD

5%

7210.49.00 STEEL, flat rolled, non-alloy steel, hot dipped galvannealed zinc coated, in coils, having ALL of the following:

- (a) yield strength NOT greater than 210 MPa;
- (b) tensile strength NOT less than 270 MPa;
- (c) total elongation NOT less than 40%;
- (d) total coating mass NOT less than 30 g/m2 and NOT greater than 70 g/m2 on each side;
- (e) in ANY of the following sizes:
  - (i) thickness 0.75 mm and width 1 390 mm;
  - (ii) thickness 0.75 mm and width 1 450 mm;
  - (iii) thickness 0.75 mm and width 1 475 mm;
  - (iv) thickness 0.75 mm and width 1 530 mm;
  - (v) thickness 0.75 mm and width 1 565 mm;
  - (vi) thickness 0.75 mm and width 1 640 mm;
  - (vii) thickness 0.76 mm and width 1 220 mm;
  - (viii) thickness 0.80 mm and width 1 350 mm;
  - (ix) thickness 0.95 mm and width 820 mm;
  - (x) thickness 1.00 mm and width 624 mm

50

For the purposes of this Order, tolerances allowable for specification (e) are:

(a) thickness +/- 10%  
 (b) width +/- 1%  
 Op. 24.12.12

- TC 1248929

Stated Use:  
 In PMV car body outer skins

Applicant: BLUESCOPE STEEL (AIS) PTY LTD

5%

## 9 TCO Applications

Commonwealth of Australia Gazette  
No TC 13/03, Wednesday, 23 Jan 2013Description of Goods including the  
Customs Tariff ClassificationSchedule 4 Item Number  
General Duty Rate

7210.49.00	<p>STEEL, flat rolled, non-alloy steel, hot dipped galvanized zinc coated, in coils, having ALL of the following:</p> <p>(a) yield strength NOT less than 190 MPa; (b) tensile strength NOT less than 340 MPa; (c) total elongation NOT less than 32%; (d) total coating mass NOT less than 30 g/m2 and NOT greater than 70 g/m2 on each side; (e) in ANY of the following sizes:</p> <p>(i) thickness 0.70 mm and width 865 mm; (ii) thickness 0.70 mm and width 980 mm; (iii) thickness 0.70 mm and width 1 225 mm; (iv) thickness 0.70 mm and width 1 244 mm; (v) thickness 0.70 mm and width 1 300 mm; (vi) thickness 0.70 mm and width 1 350 mm; (vii) thickness 0.70 mm and width 1 370 mm; (viii) thickness 0.70 mm and width 1 400 mm; (ix) thickness 0.70 mm and width 1 410 mm; (x) thickness 0.70 mm and width 1 455 mm; (xi) thickness 0.70 mm and width 1 500 mm; (xii) thickness 0.70 mm and width 1 585 mm; (xiii) thickness 0.70 mm and width 1 710 mm; (xiv) thickness 0.70 mm and width 1 720 mm; (xv) thickness 0.65 mm and width 865 mm; (xvi) thickness 0.65 mm and width 1 800 mm; (xvii) thickness 1.00 mm and width 1 160 mm</p>	50
------------	--	----

For the purposes of this Order, tolerances allowable for specification (e) are:

- (a) thickness +/- 10%  
(b) width +/- 1%  
Op. 24.12.12

- TC 1248930

Stated Use:  
In PMV car body outer skins

Applicant: BLUESCOPE STEEL (AIS) PTY LTD 5%

7210.49.00	<p>STEEL, flat rolled, non-alloy steel, hot dipped galvanized zinc coated, in coils, having ALL of the following:</p> <p>(a) yield strength NOT less than 165 MPa and NOT greater than 325 MPa; (b) tensile strength NOT less than 270 MPa; (c) total elongation NOT less than 35% and NOT greater than 50%; (d) total coating mass NOT less than 45 g/m2 and NOT greater than 65 g/m2 on each side; (e) thickness 2.00 mm and width 1 070 mm</p>	50
------------	---	----

For the purposes of this Order, tolerances allowable for specification (e) are:

- (a) thickness +/- 10%  
(b) width +/- 1%  
Op. 28.12.12

- TC 1349350

Stated Use:  
In PMV car body outer skins

Applicant: BLUESCOPE STEEL (AIS) PTY LTD

5%



## 10 TCO Applications

Commonwealth of Australia Gazette  
No TC 13/03, Wednesday, 23 Jan 2013Description of Goods including the  
Customs Tariff ClassificationSchedule 4 Item Number  
General Duty Rate

7210.49.00	STEEL, flat rolled, non-alloy steel, hot dipped galvanized zinc coated, in coils, having ALL of the following: (a) yield strength NOT less than 115 MPa and NOT greater than 305 MPa; (b) tensile strength NOT less than 270 MPa; (c) total elongation NOT less than 37% and NOT greater than 57%; (d) total coating mass NOT less than 35 g/m2 and NOT greater than 65 g/m2 on each side; (e) in ANY of the following sizes: (i) thickness 0.65 mm and width 870 mm; (ii) thickness 0.65 mm and width 930 mm; (iii) thickness 0.65 mm and width 1 150 mm; (iv) thickness 0.65 mm and width 1 640 mm; (v) thickness 0.65 mm and width 1 645 mm; (vi) thickness 0.65 mm and width 1 680 mm; (vii) thickness 0.65 mm and width 1 710 mm; (viii) thickness 0.70 mm and width 925 mm; (ix) thickness 0.70 mm and width 930 mm; (x) thickness 0.70 mm and width 1 000 mm; (xi) thickness 0.70 mm and width 1 005 mm; (xii) thickness 0.70 mm and width 1 010 mm; (xiii) thickness 0.70 mm and width 1 045 mm; (xiv) thickness 0.70 mm and width 1 455 mm; (xv) thickness 0.70 mm and width 1 485 mm; (xvi) thickness 0.70 mm and width 1 550 mm; (xvii) thickness 0.75 mm and width 1 135 mm; (xviii) thickness 0.75 mm and width 1 140 mm; (xix) thickness 0.75 mm and width 1 625 mm; (xx) thickness 0.75 mm and width 1 670 mm; (xxi) thickness 0.80 mm and width 1 060 mm; (xxii) thickness 0.80 mm and width 1 150 mm; (xxiii) thickness 0.80 mm and width 1 200 mm; (xxiv) thickness 1.00 mm and width 1 610 mm; (xxv) thickness 1.20 mm and width 1 595 mm; (xxvi) thickness 2.30 mm and width 985 mm	50
------------	--	----

For the purposes of this Order, tolerances allowable for  
specification (e) are:

- (a) thickness +/- 10%  
(b) width +/- 1  
Op. 28.12.12

- TC 1349351

Stated Use:  
In PMV car body outer skins

Applicant: BLUESCOPE STEEL (AIS) PTY LTD

5%

## 11 TCO Applications

Commonwealth of Australia Gazette  
No TC 13/03, Wednesday, 23 Jan 2013Description of Goods including the  
Customs Tariff ClassificationSchedule 4 Item Number  
General Duty Rate

7210.49.00	<p>STEEL, flat rolled, non-alloy steel, hot dipped galvanized zinc coated, in coils, having ALL of the following:</p> <p>(a) yield strength NOT less than 155 MPa and NOT greater than 295 MPa;</p> <p>(b) tensile strength NOT less than 340 MPa;</p> <p>(c) total elongation NOT less than 34%;</p> <p>(d) total coating mass NOT less than 35 g/m<sup>2</sup> and NOT greater than 65 g/m<sup>2</sup> on each side;</p> <p>(e) in ANY of the following sizes:</p> <p>(i) thickness 0.70 mm and width 830 mm;</p> <p>(ii) thickness 0.70 mm and width 855 mm;</p> <p>(iii) thickness 0.75 mm and width 840 mm;</p> <p>(iv) thickness 0.75 mm and width 855 mm;</p> <p>(v) thickness 0.75 mm and width 1 630 mm;</p> <p>(vi) thickness 0.75 mm and width 1 645 mm;</p> <p>(vii) thickness 0.75 mm and width 1 683 mm;</p> <p>(viii) thickness 0.75 mm and width 1 700 mm;</p> <p>(ix) thickness 1.20 mm and width 1 170 mm;</p> <p>(x) thickness 1.20 mm and width 1 175 mm;</p> <p>(xi) thickness 1.20 mm and width 1 198 mm;</p> <p>(xii) thickness 1.60 mm and width 1 160 mm</p>	50
------------	---	----

For the purposes of this Order, tolerances allowable for specification (e) are:

- (a) thickness +/- 10%
- (b) width +/- 1%
- Op. 28.12.12

- TC 1349352

Stated Use:  
In PMV car body outer skins

Applicant: BLUESCOPE STEEL (AIS) PTY LTD

5%

7210.49.00	<p>STEEL, flat rolled, non-alloy steel, hot dipped galvanized zinc coated, in coils, having ALL of the following:</p> <p>(a) yield strength NOT less than 235 MPa and NOT greater than 400 MPa;</p> <p>(b) tensile strength NOT less than 390 MPa;</p> <p>(c) total elongation NOT less than 28%;</p> <p>(d) total coating mass NOT less than 35 g/m<sup>2</sup> and NOT greater than 65 g/m<sup>2</sup> on each side;</p> <p>(e) in ANY of the following sizes:</p> <p>(i) thickness 2.00 mm and width 975 mm;</p> <p>(ii) thickness 2.30 mm and width 948 mm;</p> <p>(iii) thickness 2.30 mm and width 1 030 mm;</p> <p>(iv) thickness 2.30 mm and width 1 190 mm;</p> <p>(v) thickness 2.60 mm and width 1 230 mm</p>	50
------------	--	----

For the purposes of this Order, tolerances allowable for specification (e) are:

- (a) thickness +/- 10%
- (b) width +/- 1%
- Op. 28.12.12

- TC 1349354

Stated Use:  
In PMV car body outer skins

Applicant: BLUESCOPE STEEL (AIS) PTY LTD

5%

## 12 TCO Applications

Commonwealth of Australia Gazette  
No TC 13/03, Wednesday, 23 Jan 2013

Description of Goods including the Customs Tariff Classification	Schedule 4 Item Number General Duty Rate
<p>7226.92.00 STEEL, flat rolled, alloy steel, cold rolled, complying with Japanese Industrial Standard G3135 (JIS G3135), grade SPFC980Y, having ALL of the following:</p> <ul style="list-style-type: none"> <li>(a) yield strength NOT less than 580 MPa and NOT greater than 920 MPa;</li> <li>(b) tensile strength NOT less than 980 MPa;</li> <li>(c) total elongation NOT less than 11% and NOT greater than 22%;</li> <li>(d) thickness 1.40 mm and width 435 mm</li> </ul> <p>For the purposes of this Order, tolerances allowable for specification (d) are:</p> <ul style="list-style-type: none"> <li>(a) thickness +/- 10%</li> <li>(b) width +/- 1%</li> </ul> <p>Op. 28.12.12</p> <p>Stated Use: In PMV car body outer skins</p> <p>Applicant: BLUESCOPE STEEL (AIS) PTY LTD</p>	<p>50</p> <p>5%</p>
<p>7306.19.00 LINE PIPE, ELECTRIC RESISTANCE WELDED (ERW), complying with American Petroleum Institute Standard Specification 5L (API 5L) and International Standard 3183, (ISO 3183), having a diameter exceeding 168.3 mm</p> <p>Op. 18.12.12</p> <p>Stated Use: Transmission of gas in high pressure gas pipeline</p> <p>Applicant: ARROW ENERGY LTD</p>	<p>50</p> <p>5%</p>
<p>7308.90.00 SPACE FRAMES, SPHERICAL DISH, SOLAR CONCENTRATOR, having BOTH of the following:</p> <ul style="list-style-type: none"> <li>(a) maximum wind loading NOT greater than 147.6 kilometres per hour;</li> <li>(b) maximum force on base NOT greater than 170 000 kN</li> </ul> <p>Op. 21.12.12</p> <p>Stated Use: Mounting of mirror panels which focus sunlight onto DC power generation cells in concentrated photovoltaic power configurations</p> <p>Applicant: SOLAR SYSTEMS PTY LTD</p>	<p>50</p> <p>5%</p>
<p>7311.00.00 TANKS, RECEIVER, welded, having BOTH of the following:</p> <ul style="list-style-type: none"> <li>(a) maximum pressure capacity NOT greater than 19 barg;</li> <li>(b) liquid volume capacity NOT less than 145 cubic metres</li> </ul> <p>Op. 20.12.12</p> <p>Stated Use: For the supply of plant, instrument and feed air in a nitrogen generation system</p> <p>Applicant: AUSTRALIA PACIFIC LNG PROCESSING PTY LTD</p>	<p>50</p> <p>5%</p>

- TC 1349347

- TC 1248298

- TC 1248776

- TC 1248563