

COMMONWEALTH OF AUSTRALIA

Ministerial Exemption Instrument No. 2 of 2015

Customs Tariff (Anti-Dumping) Act 1975

I, KAREN LESLEY ANDREWS, Parliamentary Secretary to the Minister for Industry and Science, have considered and accepted the recommendations of the Commissioner of the Anti-Dumping Commission, the reasons for the recommendations, the material findings of fact on which the recommendations are based and the evidence relied on to support those findings in Anti-Dumping Commission Report EX0024: Exemption from dumping duties on hot rolled coil steel exported to Australia from Japan, the Republic of Korea, Malaysia and Taiwan.

Under paragraph 8(7)(b) of the *Customs Tariff (Anti-Dumping) Act 1975*, I hereby exempt the goods described in Attachment 1 (the Goods) from:

- interim dumping duty and dumping duty,

as I am satisfied that a Tariff Concession Order under Part XVA of the *Customs Act 1901* in respect of the goods is in force.

The anti-dumping measures previously applying to these goods were imposed following the then Minister for Home Affairs' consideration of *International Trade Remedies Branch Final Report No. 188* concerning the alleged dumping of hot rolled plate steel exported from Japan, the Republic of Korea, Malaysia and Taiwan.

This instrument commences on the 18th day of July 2014. The instrument is subject to review and may be revoked.

Dated this 19th day of August 2015

KAREN LESLEY ANDREWS

Parliamentary Secretary to the Minister for Industry and Science

Attachment 1

CURRENT Tariff Concession Order (TCO) for tariff classification 7208.27.00

All goods meeting the description detailed below for the current TCO are eligible for an exemption from dumping duties and countervailing duties under Ministerial Exemption Instrument No. 2 of 2015.

7208.27.00 STEEL, flat rolled, iron OR non-alloy, hot rolled, pickled, not coated, in coils, complying with Japanese Industrial Standard G3134 (JIS G3134), grade SPFH590, having ALL of the following:

- (a) yield strength NOT less than 460 MPa and NOT greater than 610 MPa;
- (b) tensile strength NOT less than 590 MPa;
- (c) elongation NOT less than 17% and NOT greater than 31%;
- (d) thickness 1.80 mm and width 1 110 mm

For the purpose of this Order, tolerances allowable for specification (d) are:

- (a) thickness +/- 10%
- (b) width +/- 1%

Op. 17.04.2014

Dec. 14.07.2014

- TC 1413447