

燁輝與燁輝 (中國) 鋁鋅鳳鋼捲規格與尺寸

Yieh Phui and Yieh Phui (China) PhuizerFan Specifications

品名 Product Name		鋁鋅鳳 (熱浸鍍 5% 鋁-鋅) 鋼捲 PhuizerFan (5%Al-Zn Coated Steel Coil)																	
規格 Specifi- cations		CNS 15236 2013			JIS G 3317 2017			ASTM A875M 2013					AS 1397 2011			EN10346 2015			
		SZACD1	SZACC	SZAC340 SZAC400 SZAC440 SZAC490 SZAC540 SZAC570	SZAH SZAC	SZAC	SZACD1	Commercial Steel Type A B C	Form- ing Steel Type A B	DDS	Struct- ural Steel Grade 230 255 275 340	Struct- ural Steel Grade 550	G3	G1 G2	G250 G300 G350 G450 G500 G550	DX51D	DX52D DX53D	S220GD S250GD S280GD S320GD S350GD	S550GD
底材 厚度 Base Steel Thickness (mm)	燁輝 Yieh Phui	0.27 1.10	0.2 1.8	0.2 1.75	1.30 4.50	0.2 1.80	0.27 1.10	0.20 4.50	0.27 1.10	0.20 4.50	0.20 2.00	0.27 1.10	0.2 1.8	0.2 4.50	0.20 4.50	0.27 1.10	0.20 4.50	0.20 4.50	0.20 1.80
	燁輝 (中國) Yieh Phui (China)	0.40 2.20	0.26 2.20	0.28 2.20	1.80 2.20	0.26 2.20	0.40 2.20	0.26 2.20	0.30 2.20	0.40 2.20	0.28 2.20	0.25 1.30	0.40 2.20	0.26 2.20	0.25 2.20	0.26 2.20	0.40 2.20	0.3 2.0	0.25 2.0
鍍層量 Coating Mass		Y08 Y35			Y08 Y10 Y12 Y18 Y20 Y22 Y25 Y27 Y35			ZGF 90 ZGF135 ZGF180 ZGF225 ZGF275 ZGF350					ZA90 ZA450			ZA 095 ZA 130 ZA 185 ZA 200 ZA 255 ZA 300			
表面精整 Surface Finish		一般鍍 5% 鋁-鋅鋅花、微細鋅花 <sup>1</sup> Regular Spangle, Minimized Spangle <sup>1</sup>																	
表面處理 Surface Treatment		鉻酸或塗油或有機樹脂 (耐指紋塗膜) 處理 Chromating Treatment, Oiled or Resin Coated (anti-fingerprint)																	
備註 Remarks		<ol style="list-style-type: none"> <li>1. 鋅花大小直徑 3mm 以上為一般鋁鋅鳳鋅花，3mm 以下為微細鋅花。</li> <li>2. 厚度、寬度、平坦度……等之公差容許範圍，依各製品規範之要求。</li> <li>3. 對各種表面精整厚度 2.0mm 以下，可再實施調質處理。</li> <li>4. 客戶訂購厚度未滿 1.6mm 之 JIS G3302 HGI 製品，其規格要求比照厚度 1.6mm JIS G3302 HGI 製品之規定。</li> <li>5. 鋼捲內徑為 508 或 610mm；外徑之最大容許值為 2000mm。</li> <li>6. 不在上述範圍之產品，如尺寸、鍍層、規格等，請以個案詢問專案開發方式進行。</li> </ol> <ol style="list-style-type: none"> <li>1. Spangle diameter above 3mm is regular spangle. Under 3mm is minimized spangle.</li> <li>2. Tolerance for thickness, width, flatness and so on conforms to individual product specification.</li> <li>3. All products with thickness 2.0mm and under can be skinpassed.</li> <li>4. The specification for thicknesses under 1.6mm for hot-rolled base metal according to JIS G3302 will be the same as for thicknesses 1.6mm and above.</li> <li>5. Coil inside diameters can be either 508mm or 610mm. Maximum coil outside diameter is 2000mm.</li> <li>6. Please make inquires to our Sales &amp; Marketing Division for products with special specifications.</li> </ol>																	