

APPENDIX 1

NMI 14/2/171

Rev 0

24/05/13



Australian Government
National Measurement Institute

Pattern Approval Number: NMI 14/2/171

Manufacturer/Make: Carlo Gavazzi

Model	Type of meter	Connection / operation	Accuracy class	Phases	Wires	Reference frequency	Reference voltage	Rated or Basic current	Maximum current	Meter constant
EM24DIN	Electronic	Transformer-operated	1	3	4	50 Hz	160(277) V AC to 480(830) V AC	- ^[1]	1 A, 5 A	Adjustable
EM24DIN	Electronic	Direct-Connected	1	3	4	50 Hz	184(318) V AC to 276(480) V AC	- ^[1]	65 A	Adjustable
EM4DIN	Electronic	Direct-Connected	1	3	4	50 Hz	400 V AC	- ^[1]	100 A	Adjustable
WM40	Electronic	Transformer-operated	0.5	3	4	50 Hz	160(277) V AC to 480(830) V AC	- ^[1]	1 A, 5 A	Adjustable
WM30	Electronic	Transformer-operated	0.5	3	4	50 Hz	160(277) V AC to 480(830) V AC	- ^[1]	1 A, 5 A	Adjustable
EM26 96	Electronic	Transformer-operated	1	3	4	50 Hz	120(208) V AC to 230(400) V AC	1 A, 5 A	10 A	Adjustable

Note [1]: Values are not specified. Various values may be applicable.