

Bradfield Road, West Lindfield NSW 2070

Interim Certificate of Approval NMI 6/10B/88

VALID FOR VERIFICATION PURPOSES UNTIL 25 NOVEMBER 2015

Issued by the Chief Metrologist under Regulation 60 of the
National Measurement Regulations 1999

This is to certify that an approval for use for trade has been granted in respect of the instruments herein described.

Grainline Model WS8030 Weighing Instrument

submitted by Grainline

1 Hartog Place

Wagga Wagga NSW 2650

NOTE: This Certificate relates to the suitability of the pattern of the instrument for use for trade only in respect of its metrological characteristics. This Certificate does not constitute or imply any guarantee of compliance by the manufacturer or any other person with any requirements regarding safety.

This approval has been granted with reference to document NMI R 76, Non-automatic weighing instruments, Parts 1 and 2, dated July 2004.

DOCUMENT HISTORY

Rev	Reason/Details	Date
0	Pattern & variant 1 approved – interim certificate issued	25/07/14
1	Pattern & variant 1 amended (validity) – interim certificate issued	14/10/14
2	Pattern & variant 1 amended (validity) – interim certificate issued	7/05/15

CONDITIONS OF APPROVAL

General

Instruments purporting to comply with this approval shall be marked with pattern approval number 'NMI 6/10B/88' and only by persons authorised by the submittor.

It is the submittor's responsibility to ensure that all instruments marked with this approval number are constructed as described in the documentation lodged with the National Measurement Institute (NMI) and with the relevant Certificate of Approval and Technical Schedule. Failure to comply with this Condition may attract penalties under Section 19B of the National Measurement Act and may result in cancellation or withdrawal of the approval, in accordance with document NMI P 106.

Auxiliary devices used with this instrument shall comply with the requirements of General Supplementary Certificate No S1/0B.

The pattern as approved herein or with substitute approved load cells and/or approved indicators and in other capacities, or with different platform sizes, shall comply with General Certificate of Approval No 6B/0.

Note: New instruments manufactured under this approval shall only use load cells and/or indicators with current Supplementary Certificates of Approval.

1. Description of Pattern

approved on 25/07/14

A Grainline model WS8030 class non-automatic self-indicating weighing instrument of 30 000 kg maximum capacity and approved for use with up to 3000 verification scale intervals.

The model WS8030 basework has the platform of 8 m \times 3 m fully supported by eight Flintec model RC3-30t-C3 load cells of 30 000 kg maximum capacity. The load cells are described in the documentation of approval NMI S368.

A Leon Engineering model LD 5290 digital indicator. The indicator is described in the documentation of approval NMI S676.

Where the instrument is intended to be installed as a weighbridge, it shall be ensured that all relevant weighbridge requirements of the National Measurement Legislation are met (e.g. in relation to weighbridge approaches, visibility and the location of the weighbridge indicator and platform). This approval does not certify that such requirements have (or can be) met.

2. Description of Variant 1

approved on 25/07/14

Other Grainline model WSxxyy series instruments, as single interval, multiple range or multi-interval instruments similar to the pattern, of other capacities subject to approval parameters of the load cells and indicator, and compliance with General Certificate of Approval No 6B/0.

The model number may contain suffixes indicating length and width of the particular model version (e.g. 'WS18030' indicates instrument with a 18 m \times 3 m platform).

The platform is fully supported by no less than 4 and with up to 12 NMI approved load cells. Instruments may be in capacities of:

- 100 kg up to 1499 kg;
- 1500 kg up to 14 999 kg;
- 15 000 kg up to 149 999 kg; and
- 150 000 kg and above,

using approved load cells and an approved digital indicator (in accordance with General Certificate of Approval No 6B/0).

Instruments are approved for use with up to 4000 verification scale intervals (subject to the approval parameters of the load cells and indicator).

Instruments used with more than 3000 verification scale intervals shall be provided with wind protection in accordance with clause **4. Wind Effects** of General Certificate of Approval No 6B/0.

Signed by a person authorised by the Chief Metrologist to exercise their powers under Regulation 60 of the *National Measurement Regulations 1999*.

Dr A Rawlinson

~ End of Document ~