



Australian Government

National Measurement
Institute

Bradfield Road, West Lindfield NSW 2070

Interim Provisional Supplementary Certificate of Approval NMI PS571

VALID FOR VERIFICATION PURPOSES UNTIL 30 JULY 2013

Issued by the Chief Metrologist under Regulation 60
of the
National Measurement Regulations 1999

This is to certify that an approval for use for trade has been granted in respect of the instruments herein described.

Fujitsu Model OnePOS Point of Sale (POS) System

submitted by Fujitsu Australia Limited
Level 16, 15 Blue Street
NORTH SYDNEY NSW 2060

NOTE: This Certificate relates to the suitability of the pattern of the instrument for use for trade only in respect of its metrological characteristics. This Certificate does not constitute or imply any guarantee of compliance by the manufacturer or any other person with any requirements regarding safety.

DOCUMENT HISTORY

Rev	Reason/Details	Date
0	Pattern provisionally approved – interim certificate issued	31/07/12
1	Pattern amended (minor transaction printing change) – interim certificate issued	7/08/12
2	Pattern amended (validity date) – interim certificate issued	21/12/12
3	Pattern amended (software version & validity date) – interim certificate issued	19/04/13

CONDITIONS OF APPROVAL

General

Instruments purporting to comply with this approval shall be marked with approval number 'NMI PS571' and only by persons authorised by the submittor.

It is the submittor's responsibility to ensure that all instruments marked with this approval number are constructed as described in the documentation lodged with the National Measurement Institute (NMI) and with the relevant Certificate of Approval and Technical Schedule. Failure to comply with this Condition may attract penalties under Section 19B of the National Measurement Act and may result in cancellation or withdrawal of the approval, in accordance with document NMI P 106.

Special

Certain aspects of this instrument (in particular transaction record printing formats) are able to be configured by the user. Whilst NMI believes that acceptable formats can be achieved for typical basic sales modes, it is also possible for the instrument to be configured to produce unacceptable formats, and use of some formats may be inappropriate for different sales modes. It is the responsibility of the user to ensure that acceptable and appropriate formats are used in any particular situation.

Special Conditions of Approval: (Provisional Approval)

The locations and/or serial numbers of instruments be obtained from the National Measurement Institute. The submitter shall advise NMI in writing of the proposed location and/or serial number of each instrument prior to it being initially verified.

Instruments purporting to comply with this approval shall be marked with approval number 'NMI PS571' and only by persons authorised by the submitter. (Note: The 'P' in the approval number may be a temporary marking.)

The approval will remain provisional pending completion of satisfactory testing and evaluation.

In the event of unsatisfactory performance the approval may be cancelled (or altered).

The submitter shall implement such modifications as required by NMI. In the event that such modifications (if any are required by NMI) are not made to the satisfaction of NMI, this approval may be withdrawn.

1. Description of Pattern

approved on 31/7/12

A Fujitsu model OnePOS point of sale (POS) system to provide certain additional facilities for transactions when interfaced to compatible (#) NMI-approved measuring instruments granted with reference to document NMI M7.

1.1 Key Features

- The system provides point of sale arrangements for a Magellan SL model 8202 self-indicating non-automatic weighing instrument (approval NMI/NSC 6/4C/201) or other compatible (#) NMI-approved measuring instruments.
 - The system receives measurement data from the output interface of the approved measuring instrument and computes prices using a product look up (PLU) facility.
 - The system computes total price for multiple items including non-measured items and is approved for use for transactions direct to public.
 - Pre-determined measurement data is able to be entered manually and this **may or may not** be indicated as such on a printed transaction record.
 - The system is able to apply a preset tare up to the maximum capacity of the approved measuring instrument.
 - The POS controllers may be connected in a network to share common PLU data, for totalisation, and to accumulate and retrieve management information.
- (#) 'Compatible' is defined to mean that no additions/changes to the hardware/software specified in this approval are required for satisfactory operation of the system.

1.2 System Description

The Fujitsu model OnePOS point of sale (POS) system (Figure 1) comprises:

(i) POS Controller

The Fujitsu model OnePOS POS controller comprises an NCR model RealPOS 7457 or equivalent (*) PC-based device that operates a Microsoft Windows operating system running OnePos version 003.xxx.xxx software. The software version number is displayed in the lower right corner of the operator display.

(ii) Electronic Indications

An NCR model 5964 touch sensitive computer monitor or equivalent (*) is connected to the POS controller to provide an indication for the operator.

An NCR model 5942 computer monitor or equivalent (*) is connected to the controller and provides an indication for the customer.

(iii) Printing Devices

An Epson model TM-H5000II printer or equivalent (*) is connected to the controller to provide transaction record printing facility.

(*) 'Equivalent' is defined to mean other proprietary equipment of the same or better specifications requiring no changes to the software specified in this approval for satisfactory operation of the system.

(iv) Additional System Facilities

In addition, the system may include other facilities including point of sale cash drawers, magnetic card and/or barcode reader and electronic funds transfer (EFT). The facilities shall not interact with the system in a way that would cause an incorrect indication of the measured quantity or price.

TEST PROCEDURE

The POS system shall be tested for compliance with the requirements of General Supplementary Certificate No S1/0/A dated 20/03/92, as follows:

Testing requires a minimum of 5 checks spanning the measurement range of the measuring instrument. For each check, ensure the device is correctly:

- repeating the result of the primary indicator; and/or
- summing several primary indicators; and/or
- printing the results.

Ensure the printed format and the display format is in compliance with General Supplementary Certificate No S1/0/A.

Checks shall be conducted to ensure that the device will not print above the approved maximum capacity or below zero.

Perform a display segment check for indicators with this function.

For network systems, an additional check is required to ensure that the measurement data printed on the transaction record is correctly reproduced from each device connected in the network.

Signed by a person authorised by the Chief Metrologist to exercise their powers under Regulation 60 of the *National Measurement Regulations 1999*.



Dr A Rawlinson