

Australian Government

National Measurement Institute Bradfield Road, West Lindfield NSW 2070

Interim Supplementary Certificate of Approval NMI S607

VALID FOR VERIFICATION PURPOSES UNTIL 23 MAY 2014

Issued by the Chief Metrologist under Regulation 60 of the National Measurement Regulations 1999

This is to certify that an approval for use for trade has been granted in respect of the instruments herein described.

QUORION Model QTouch 2 Point of Sale (POS) System

submitted by	QUORiON Pty Ltd Unit 22, 7-9 Percy Street		
	Auburn	NSW	2144

NOTE: This Certificate relates to the suitability of the pattern of the instrument for use for trade only in respect of its metrological characteristics. This Certificate does not constitute or imply any guarantee of compliance by the manufacturer or any other person with any requirements regarding safety.

This approval has been granted with reference to document NMI M7, *Pattern Approval Specifications for Point of Sale Systems*, dated June 2012.

Rev	Reason/Details	Date
0	Pattern & variant 1 provisionally approved – interim certificate issued	26/10/12
1	Pattern & variant 1 amended (validity date) – interim certificate issued	17/01/13
2	Pattern & variant 1 amended (validity date) – interim certificate issued	24/04/13
3	Pattern & variant 1 approved – interim certificate issued	23/10/13
4	Pattern & variant 1 amended (validity date) – interim certificate issued	21/02/14

DOCUMENT HISTORY

CONDITIONS OF APPROVAL

General

Instruments purporting to comply with this approval shall be marked with pattern approval number 'NMI S607' and only by persons authorised by the submittor.

Instruments purporting to comply with this approval and currently marked 'NMI PS607' may be re-marked 'NMI S607' but only by persons authorised by the submittor.

It is the submittor's responsibility to ensure that all instruments marked with this approval number are constructed as described in the documentation lodged with the National Measurement Institute (NMI) and with the relevant Certificate of Approval and Technical Schedule. Failure to comply with this Condition may attract penalties under Section 19B of the National Measurement Act and may result in cancellation or withdrawal of the approval, in accordance with document NMI P 106.

Auxiliary devices used with this instrument shall comply with the requirements of General Supplementary Certificate No S1/0B.

Special

Certain aspects of this instrument (in particular transaction record printing formats) are able to be configured by the user. Whilst NMI believes that acceptable formats can be achieved for typical basic sales modes, it is also possible for the instrument to be configured to produce unacceptable formats, and use of some formats may be inappropriate for different sales modes. It is the responsibility of the user to ensure that acceptable and appropriate formats are used in any particular situation.

1. Description of Pattern provisionally approved on 26/10/12 approved on 23/10/13

A QUORION model QTouch 2 system to provide certain additional facilities for transactions when interfaced to compatible (#) NMI-approved point of sale systems granted with reference to document NMI M7.

1.1 Key Features

- The system provides point of sale arrangements for a CAS model PD-II self-indicating non-automatic weighing instrument (approval NMI 6/4C/237) or other compatible (#) NMI-approved measuring instruments.
- The system receives measurement data from the output interface of the approved measuring instrument and computes prices using a product look up (PLU) facility.
- The system computes total price for multiple items including non-measured items and is approved for use for transactions direct to the public.
- The system is able to apply a preset tare value up to the maximum capacity of the approved measuring instrument. Preset tare values may be keyboard-entered or stored (e.g. within a PLU facility).
- The POS controllers may be connected in a network to share common PLU data, for totalisation, and to accumulate and retrieve management information.
- (#) 'Compatible' is defined to mean that no additions/changes to the hardware/software specified in this approval are required for satisfactory operation of the system.

1.2 System Description

The QUORiON model QTouch 2 point of sale (POS) system comprises:

(i) POS Controller

The POS controller comprises a QUORiON model QTouch 2 or equivalent (*) POS device that operates a Linux operating system running version QCxxx software. The software version number is displayed by typing '305' then 'TYPE' while in Program ('P') mode.

(ii) Electronic Indications

Indications shall satisfy the requirements of document NMI M7, *Pattern Approval Specifications for Point of Sale Systems*.

The QUORiON model QTouch 2 has an integral touch sensitive display to provide an indication for the operator and a Bixolon model BCD-1000 or equivalent (*) external 2-line display to provide an indication for the customer.

Information additional to that required by document NMI M7, including totalisation details and product images, may also be indicated.

(iii) **Printing Devices**

Transaction records shall satisfy the requirements of document NMI M7, *Pattern Approval Specifications for Point of Sale Systems*.

An Optimas model J80 thermal receipt printer or equivalent (*) is connected to the controller to provide transaction record printing facility.

(*) 'Equivalent' is defined to mean other proprietary equipment of the same or better specifications requiring no changes to the software specified in this approval for satisfactory operation of the system.

(iv) Additional System Facilities

In addition, the system may include other facilities including point of sale cash drawers, magnetic card and/or barcode reader and electronic funds transfer (EFT), etc. The facilities shall not interact with the system in a way that would cause an incorrect indication of the measured quantity or price.

1.3 Descriptive Markings

The POS controller is marked in a clear and permanent manner, in one location, with the following information:

Submittor's name or mark	
Serial number or other unique identifier	
Pattern approval number	NMI S607

1.4 Family of Devices

Certain other models in the QUORiON QTouch series of POS devices as listed below and which are similar to the pattern, in various configurations of the features outlined in clause **1.2 (iv) Additional System Facilities**.

Approved models (and the software version/s (#) used), are:

- QTOUCH 3 (QLxxx or QAxxx); and
- QTOUCH 10 (QAxxx).

Some models have a conventional keyboard rather than a touch sensitive screen.

2. Description of Variant 1 provisionally approved on 26/10/12 approved on 23/10/13

Certain models of QUORiON cash registers as listed below and which are similar to the pattern, in various configurations of the features outlined in clause **1.2 (iv)** Additional System Facilities.

Approved models (and the software version (#) used), are:

- QPOS (QLxxx);
- QMP 2044 (H4xxx), QMP 2164 (H4xxx), QMP 2264 (H4xxx), QMP 5286 (F6xxx) & QMP 5496 (F6xxx); and
- CR 1020 (E0xxx) & CR 1240 (E0xxx).

Some models have a conventional keyboard rather than a touch sensitive screen.

(#) For display and print the software version number on all QUORiON Qtouch series POS devices or cash registers:

Program (P) mode \rightarrow 305 \rightarrow Type ('PLU' button on cash registers)

TEST PROCEDURE

The POS system shall be tested in addition to any tests specified in the approval documentation for the measuring instrument/s to which the POS system is connected, as appropriate

The POS system shall be tested in the normal operational mode of the instrument and device, not in 'training mode' or any other management mode.

Maximum Permissible Error

The maximum permissible error for price computation is ± 0.5 cent.

TESTS

- 1. Check the software version number/s.
- 2. Check that the POS system faithfully reproduces the measurement data in the same units and scale interval as the connected approved measuring instrument, e.g. test by using a PLU without a stored tare.
- 3. Check that the system performs correct price computation, and computes and indicates a correct unrounded subtotal. For cash payment methods, check that any rounding calculation is correct.
- 4. Perform a measurement with a preset tare applied and confirm that the POS system correctly calculates and indicates a net measurement result.
- 5. For network systems check to ensure that the measurement data printed on the transaction record is correctly reproduced.
- 6. Ensure that electronic indications and printed information are in accordance with document NMI M7.

Signed by a person authorised by the Chief Metrologist to exercise their powers under Regulation 60 of the *National Measurement Regulations 1999*.

Dr A Rawlinson

~ End of Document ~