



Australian Government
Department of Industry,
Innovation and Science

National Measurement Institute

36 Bradfield Road, West Lindfield NSW 2070

Supplementary Certificate of Approval NMI S583

Issued by the Chief Metrologist under Regulation 60
of the
National Measurement Regulations 1999

This is to certify that an approval for use for trade has been granted in respect of the instruments herein described.

Uniwell Model AX-3000 Point of Sale (POS) System

submitted by Uniwell POS Australia Pty Ltd
Unit 24, 280 New Line Road
DURAL NSW 2158

NOTE: This Certificate relates to the suitability of the pattern of the instrument for use for trade only in respect of its metrological characteristics. This Certificate does not constitute or imply any guarantee of compliance by the manufacturer or any other person with any requirements regarding safety.

This approval has been granted with reference to document NMI M7, *Pattern Approval Specifications for Point of Sale Systems*, dated June 2012.

This approval becomes subject to review on 1/05/24, and then every 5 years thereafter.

DOCUMENT HISTORY

Rev	Reason/Details	Date
0	Pattern provisionally approved – interim certificate issued	16/08/12
1	Pattern amended (validity date) – interim certificate issued	30/11/12
2	Pattern amended (validity date) – interim certificate issued	28/02/13
3	Pattern approved – certificate issued	5/04/13
4	Pattern amended (replace Figure 4) – certificate issued	24/04/13
5	Variants 1 & 2 approved – certificate issued	16/10/14
6	Variant 3 approved – certificate issued	3/05/19
7	Variant 1 amended (model description) – certificate issued	19/09/19

CONDITIONS OF APPROVAL

General

Instruments purporting to comply with this approval shall be marked with pattern approval number 'NMI S583' and only by persons authorised by the submitter.

Instruments purporting to comply with this approval and currently marked 'NMI PS583' may be re-marked 'NMI S583' but only by persons authorised by the submitter.

It is the submitter's responsibility to ensure that all instruments marked with this approval number are constructed as described in the documentation lodged with the National Measurement Institute (NMI) and with the relevant Certificate of Approval and Technical Schedule. Failure to comply with this Condition may attract penalties under Section 19B of the National Measurement Act and may result in cancellation or withdrawal of the approval, in accordance with document NMI P 106.

Special

Certain aspects of this instrument (in particular transaction record printing formats) are able to be configured by the user. Whilst NMI believes that acceptable formats can be achieved for typical basic sales modes, it is also possible for the instrument to be configured to produce unacceptable formats, and use of some formats may be inappropriate for different sales modes. It is the responsibility of the user to ensure that acceptable and appropriate formats are used in any particular situation.

Signed by a person authorised by the Chief Metrologist
to exercise their powers under Regulation 60 of the
National Measurement Regulations 1999.



Mario Zamora

Ag Manager
Policy and Regulatory Services

TECHNICAL SCHEDULE No S583

1. Description of Pattern **provisionally approved on 16/08/12**
approved on 5/04/13

A Uniwell model AX-3000 point of sale (POS) system to provide certain additional facilities for transactions when interfaced to compatible (#) NMI-approved measuring instruments.

1.1 Key Features

- The system provides point of sale arrangements for a CAS model PD-II self-indicating non-automatic weighing instrument (approval NMI 6/4C/237) or other compatible (#) NMI-approved measuring instruments.
 - The system receives measurement data from the output interface of the approved measuring instrument and computes prices using a product look up (PLU) facility.
 - The system computes total price for multiple items including non-measured items and is approved for use for transactions direct to public.
 - Manually entered measurement data shall be indicated as such on a printed transaction record.
 - The system is able to apply a preset tare value up to the maximum capacity of the approved measuring instrument. Preset tare values may be keyboard-entered or stored (e.g. within a PLU facility).
 - The POS controllers may be connected in a network to share common PLU data, for totalisation, and to accumulate and retrieve management information
- (#) 'Compatible' is defined to mean that no additions/changes to the hardware/software specified in this approval are required for satisfactory operation of the system.

1.2 System Description

The Uniwell model AX-3000 point of sale (POS) system (Figure 1) comprises:

(i) POS Controller

The Uniwell model AX-3000 POS controller that operates a Uniwell operating system running AX-3000 version 3.x software. The software version number is displayed by exiting 'Sales Mode', then entering a code number (obtained from the store manager), and then pressing 'Sign on', then 'Program', then 'System' and then the 'System Information' button.

(ii) Electronic Indications

Indications shall satisfy the requirements of document NMI M7, *Pattern Approval Specifications for Point of Sale Systems*.

The Uniwell model AX-3000 POS controller has an integral touch sensitive display to provide an indication for the operator (Figure 2).

A Uniwell model WD-202 2-line display or equivalent (*) is connected to the controller and provides an indication for the customer (Figure 3).

(iii) Printing Devices

Transaction records shall satisfy the requirements of document NMI M7, *Pattern Approval Specifications for Point of Sale Systems*.

An Epson model TM-T88 printer or equivalent (*) is connected to the controller to provide transaction record printing facility. A typical record is shown in Figure 4.

(iv) Additional System Facilities

In addition, the system may include other facilities including point of sale cash drawers, magnetic card and/or barcode reader and electronic funds transfer (EFT), etc. The facilities shall not interact with the system in a way that would cause an incorrect indication of the measured quantity or price.

1.3 Verification Provision

Provision is made for the application of a verification mark.

1.4 Descriptive Markings

The POS controller is marked in a clear and permanent manner, in one location, with the following information:

Submittor's name or mark
Serial number or other unique identifier
Pattern approval number	NMI S583

1.5 Family of Devices

The Uniwell DX series of devices as listed below are similar to the pattern, in various configurations of the features outlined in clause **1.2 (iv) Additional System Facilities**.

Approved models (and the software version used) are:

- models DX915 and DX895 (version 8.5x software); and
- model DX795 (version 1.x software).

2. Description of Variant 1

**approved on 16/10/14
amended on 19/09/19**

The Uniwell HX series of devices as listed below are similar to the pattern.

Approved models (and the software version used) are:

- models HX1500, HX4000 and HX4500 (version 1.x software)

A Lenovo model LT1421 computer monitor or equivalent (*) is connected to the controller and provides an alternative indication for the customer (Figure 5) as outlined in clause **1.2 (ii) Electronic Indications**.

- (*) 'Equivalent' is defined to mean other proprietary equipment of the same or better specifications requiring no changes to the software specified in this approval for satisfactory operation of the system.

3. Description of Variant 2

approved on 16/10/14

The series of systems described in the pattern may operate Uniwell software operating legally relevant version 'SCM version 1.00' software module. Non-legally relevant components of the software may also be shown as a second version number.

The software version number is displayed by exiting 'Sales Mode', then entering a code number (obtained from the store manager), and then pressing 'Sign on', then 'Program', then 'System' and then the 'System Information' button.

4. Description of Variant 3

approved on 3/05/19

The Uniwell HX series of devices as listed below are similar to the pattern.

Approved models (and the software version used) are:

- models HX2500 (Figure 6a), HX3500, HX5500 (Figure 6b) and HX6500 (version 1.x software)

TEST PROCEDURE No S583

The POS system shall be tested in addition to any tests specified in the approval documentation for the measuring instrument/s to which the POS system is connected, as appropriate

The POS system shall be tested in the normal operational mode of the instrument and device, not in 'training mode' or any other management mode.


Maximum Permissible Error

The maximum permissible error for price computation is ± 0.5 cent.

TESTS

1. Check the software version number/s.
2. Check that the POS system faithfully reproduces the measurement data in the same units and scale interval as the connected approved measuring instrument, e.g. test by using a PLU without a stored tare.
3. Check that the system performs correct price computation, and computes and indicates a correct unrounded subtotal. For cash payment methods, check that any rounding calculation is correct.
4. Perform a measurement with a preset tare applied and confirm that the POS system correctly calculates and indicates a net measurement result.
5. Manually enter some pre-determined measurement data and ensure that the printed transaction record clearly indicates the transaction as such.
6. For network systems check to ensure that the measurement data printed on the transaction record is correctly reproduced.
7. Ensure that electronic indications and printed information are in accordance with document NMI M7.

FIGURE S583 – 1



Uniwell Model AX-3000 Point of Sale (POS) System

FIGURE S583 – 2



Typical Operator Screen

FIGURE S583 – 3



Typical Customer Display

FIGURE S583 – 4



A Typical Receipt

FIGURE S583 – 5



Typical Alternate Customer display

FIGURE S583 – 6



(a) HX-2500



(b) HX-5500

Uniwell HX series Models (Variant 3)

~ End of Document ~