

Australian Government

Department of Industry, Science and Resources National Measurement Institute



HC

CERTIFIED REFERENCE MATERIAL CERTIFICATE OF ANALYSIS

NMIA D1029: (±)-2-Chloromethamphetamine hydrochloride

Report ID: D1029.2023.01

Chemical Formula: C10H14CIN.HCI

Molecular Weight: 220.1 g/mol (HCl), 183.7 g/mol (base)

Certified value

Batch No.	CAS No.	Purity (mass fraction)
14-D-29	14471-45-5 (HCI) 4302-93-6 (base)	99.7 ± 0.5%

The uncertainty has been calculated according to ISO Guide 35 and is stated at the 95% confidence limit (k = 2).

IUPAC name: 1-(2-Chlorophenyl)-*N*-methyl-2-propanamine hydrochloride (1:1).

Expiration of certification: The property values are valid till 27 March 2028, five years from the date of re-certification provided the **unopened** material is handled and stored in accordance with the recommendations below. The material as issued in the unopened container and stored as recommended below should be suitable for use beyond this date, subject to confirmation of batch stability from the issuing body. The expiry date/shelf life does not apply to sample bottles that have been opened. In such cases it is recommended that the end-user conduct their own in-house stability trials.

Description: White powder prepared by synthesis and certified for identity and purity by NMIA. Packaged in amber glass bottles with a septum and crimped aluminium cap or screw top cap.

Intended use: This certified reference material is suitable for use as a primary calibrator.

Instructions for use: Equilibrate the bottled material to room temperature before opening.

Recommended storage: When not in use this material should be stored at or below 25 °C in a closed container in a dry, dark area.

Metrological traceability: The certified purity value is traceable to the SI unit for mass (kg) through Australian national standards via balance calibration. In the mass balance approach all impurities are quantified as a mass fraction and subtracted from 100%. Quantitative NMR provides an independent direct measure of the mass fraction of the analyte of interest, calibrated with an internal standard certified for purity (mass fraction).

Stability: This material has demonstrated stability over a minimum period of five years. The measurement uncertainty at the 95% confidence interval includes a stability component which has been estimated from annual stability trials.

The long-term stability of the compound in solution has not been examined.

Homogeneity assessment: The homogeneity of the material was assessed using purity assay by GC-FID on seven randomly selected 1-2 mg sub samples of the material. The material was judged to be sufficiently homogeneous at this level of sampling as the variation in analysis results between samples was not significantly different at a 95% confidence level from that observed on repeat analysis of the same sample.

Safety: Treat as a hazardous substance. Use appropriate work practices when handling to avoid skin or eye contact, ingestion or inhalation of dust. Refer to the provided safety data sheet.

Report ID: D1029.2023.01 Product release date: 15 October 2014

measurement.gov.au

S.R. Davies

Dr Stephen R. Davies, Team Leader, Chemical Reference Materials, NMI. 26 April 2023

This report supersedes any issued prior to 26 April 2023.

NATA Accreditation No. 198 / Corporate Site No. 14214.

Legal notice: Terms and Conditions associated with the provision of this reference material can be found on the NMIA website.

Characterisation Report:

The identity was confirmed by a range of spectroscopic techniques, NMR, IR and MS. The certified purity value was obtained from a combination of traditional analytical techniques and quantitative nuclear magnetic resonance (qNMR). The techniques used in the mass balance approach include GC-FID, Karl Fischer analysis and ¹H NMR spectroscopy. The purity value is calculated as per Equation 1.

Purity = $(100 \% - I_{ORG}) \times (100 \% - I_{VOL} - I_{NVR})$ Equation 1

 I_{ORG} = Organic impurities of related structure, I_{VOL} = volatile impurities, I_{NVR} = non-volatile residue

The certified purity value by qNMR was obtained using the one-proton multiplet at 3.6 ppm measured against a certified internal standard of maleic acid.

Supporting evidence is provided by elemental microanalysis.

GC-FID:	Instrument: Column: Program: Injector: Detector Temp: Carrier: Split ratio: Relative mass fraction of	Varian CP-3800 VF-1MS, 30 m \times 0.32 mm l.D. \times 0.25 μ m 80 °C (1 min), 10 °C/min to 180 °C, 30 °C/min to 300 °C (3 min) 200 °C 320 °C Helium 20/1 of the main component as the free base:	
	Initial analysis:	Mean = 99.8%, s = 0.01% (7 sub samples in duplicate, September 2014)	
GC-FID:	Instrument: Column: Program:	Varian CP-3800, Agilent 8890 HP-1, 30 m × 0.32 mm l.D. × 0.25 μ m 80 °C (1 min), 10 °C/min to 180 °C, 30 °C/min to 300 °C (3 min) [2015, 2023] or 80 °C (1 min), 10 °C/min to 180 °C, 30 °C/min to 280 °C (10 min) [2016]	
	Injector:	200 °C	
	Detector Temp: Carrier:	320 °C Helium	
	Split ratio:	20/1	
	Relative mass fraction of the main component as the free base:		
	Initial analysis: Re-analysis: Re-analysis: Re-analysis:	Mean = 99.9%, s = 0.01% (5 sub samples in duplicate, August 2015) Mean = 99.9%, s = 0.02% (5 sub samples in duplicate, August 2016) Mean = 99.9%, s = 0.01% (5 sub samples in duplicate, November 2017) Mean = 99.8%, s = 0.01% (7 sub samples in duplicate, March 2023)	
Karl Fischer analysis:		Moisture content ≤ 0.1% mass fraction (September 2014 - March 2023)	
QNMR:	Instrument: Field strength: Solvent: Internal standard: Initial analysis:	Bruker Avance-III-500 500 MHz D_2O (4.79 ppm) Maleic acid (98.7% mass fraction) Mean (3.60 ppm) = 99.7%, s = 0.2% (3 sub samples, September 2014)	

measurement.gov.au

Spectroscopic and other characterisation data

GC-MS:	Instrument: Column: Program: Injector: Split ratio: Transfer line temp: Carrier: Scan range:	Agilent 6890/5973 TG-1MS, 30 m x 0.25 mm l.D. x 0.25 μm 60 °C (1 min), 10 °C/min to 300 °C (3 min) 250 °C 20/1 280 °C Helium 50-550 <i>m/z</i>
		e free base is reported with the major peaks in the mass spectra. The latter are reported and (in brackets) as a percentage relative to the base peak.
	Free base (10.3 min):	184 (M ⁺ -H, 2), 182 (M ⁺ -H, 6), 170 (6), 168 (17), 127 (14), 125 (39), 117 (16), 115 (19), 89 (32), 58 (100), 42 (18) <i>m/z</i>
ESI-MS:	Instrument: Operation: Ionisation: EM voltage: Cone voltage: Peak:	Micromass Quatro LC Micro Positive ion mode, direct infusion at 10 μL/min ESI spray voltage at 3.5 kV positive ion 650 V 10 V 186.3 (M ^{Cl37} +H ⁺), 184.1 (M ^{Cl35} +H ⁺) <i>m/z</i>
IR:	Instrument: Range: Peaks:	Bruker Alpha Platinum ATR 4000-400 cm ⁻¹ , neat 2962, 2936, 2840, 2722, 2458, 2436, 1493, 1474, 1425, 1387, 1085, 1069, 1046, 1014, 800, 665, 463 cm ⁻¹
¹ H NMR:	Instrument: Field strength: Solvent: Spectral data:	Bruker Avance III-500 500 MHz D_2O (4.79 ppm) δ 1.26 (3H, d, J = 6.6 Hz), 2.71 (3H, s), 2.97 (1H, dd, J = 8.4, 13.7 Hz), 3.23 (1H, dd, J = 6.1, 13.8 Hz), 3.60 (1H, m), 7.29-7.36 (3H, m), 7.45-7.48 (1H, m) ppm Isopropanol estimated at 0.14% mass fraction was observed in the ¹ H NMR
¹³ C NMR:	Instrument: Field strength: Solvent: Spectral data:	Bruker Avance III-500 125 MHz D ₂ O δ 14.8, 30.0, 36.5, 55.0, 127.4, 129.2, 129.8, 131.9, 133.3, 133.8 ppm
Melting point:		152-154 °C
Microanalysis:	Found: Calculated:	C = 54.7%; H = 6.9%; N = 6.4%; Cl% = 32.1% (September, 2014) C = 54.6%; H = 6.9%; N = 6.4%; Cl% = 32.2% (Calculated for $C_{10}H_{14}CIN.HCI$)