

Australian Government

Department of Industry, Science and Resources

## National Measurement Institute



HO

CH<sub>3</sub>C

HO

 $CH_3$ 

. С(СН<sub>3</sub>)<sub>3</sub>



# CERTIFIED REFERENCE MATERIAL CERTIFICATE OF ANALYSIS

# NMIA D932: Buprenorphine

Report ID: D932.2020.03 (Bottled 150915)

Chemical Formula: C<sub>29</sub>H<sub>41</sub>NO<sub>4</sub>

Molecular Weight: 467.6 g/mol

## **Certified value**

Batch No.	CAS No.	Purity (mass fraction)
08-D-13	52485-79-7	99.6 ± 0.3%

The uncertainty has been calculated according to ISO Guide 35 and is stated at the 95% confidence limit (k = 2).

**IUPAC name:** (5α,6β,14β,18R)-17-(Cyclopropylmethyl)-18-[(2S)-2-hydroxy-3,3-dimethyl-2-butanyl]-6-methoxy-18,19-dihydro-4,5epoxy-6,14-ethenomorphinan-3-ol

**Expiration of certification:** The property values are valid till 29 June 2030, i.e. ten years from the date of re-certification provided the **unopened** material is handled and stored in accordance with the recommendations below. The material as issued in the unopened container and stored as recommended below should be suitable for use beyond this date, subject to confirmation of batch stability from the issuing body. The expiry date/shelf life does not apply to sample bottles that have been opened. In such cases it is recommended that the end-user conduct their own in-house stability trials.

**Description:** Off-white powder sourced from an external supplier, certified for identity and purity by NMIA. Packaged in amber glass bottles with a septum and crimped aluminium cap or screw top cap.

Intended use: This certified reference material is suitable for use as a primary calibrator.

Instructions for use: Equilibrate the bottled material to room temperature before opening.

Recommended storage: When not in use this material should be stored at or below 25 °C in a closed container in a dry, dark area.

**Metrological traceability:** The certified purity value is traceable to the SI unit for mass (kg) through Australian national standards via balance calibration. In the mass balance approach all impurities are quantified as a mass fraction and subtracted from 100%.

**Stability:** This material has demonstrated stability over a minimum period of three years. The measurement uncertainty at the 95% confidence interval includes a stability component which has been estimated from annual stability trials. The long-term stability of the compound in solution has not been examined.

**Homogeneity assessment:** The homogeneity of the material was assessed using purity assay by GC-FID on five randomly selected 1-2 mg sub samples of the material. The material was judged to be sufficiently homogeneous at this level of sampling as the variation in analysis results between samples was not significantly different at a 95% confidence level from that observed on repeat analysis of the same sample.

**Safety:** Treat as a hazardous substance. Use appropriate work practices when handling to avoid skin or eye contact, ingestion or inhalation of dust. Refer to the provided safety data sheet.

Report ID: D932.2020.03 (Bottled 150915) Product release date: 28 November 2008

S.R. Davies

Dr Stephen R. Davies, Team Leader, Chemical Reference Materials, NMI. 19 September 2022

This report supersedes any issued prior to 19 September 2022.

NATA Accreditation No. 198 / Corporate Site No. 14214.

**CIPM MRA notice:** This certificate is consistent with the capabilities that are included in Appendix C of the CIPM MRA drawn up by the CIPM. Under the CIPM MRA, all participating institutes recognize the validity of each other's calibration and measurement certificates for the quantities, ranges and measurement uncertainties specified in Appendix C. The "CIPM MRA Logo" and this statement attest only to the measurement(s) applied for determining the certified values on the certificate (for details see <a href="http://www.bipm.org">http://www.bipm.org</a>).

Legal notice: Terms and Conditions associated with the provision of this reference material can be found on the NMIA website.

#### **Characterisation Report:**

The identity was confirmed by a range of spectroscopic techniques, NMR, IR and MS. The certified purity value was obtained by mass balance from a combination of traditional analytical techniques, including GC-FID, thermogravimetric analysis, Karl Fischer analysis and <sup>1</sup>H NMR spectroscopy. The purity value is calculated as per Equation 1.

Purity = (100 % - I<sub>ORG</sub>) x (100 % - I<sub>VOL</sub> - I<sub>NVR</sub>)

Equation 1

 $I_{ORG}$  = Organic impurities of related structure,  $I_{VOL}$  = volatile impurities,  $I_{NVR}$  = non-volatile residue.

Supporting evidence is provided by elemental microanalysis.

GC-FID:	Instrument:	Agilent 6890N
	Column:	HP-1, 30 m x 0.32 mm l.D. x 0.25 μm
	Program:	180 °C (1 min), 30 °C/min to 300 °C (10 min)
	Injector:	250 °C
	Detector Temp:	320 °C
	Carrier:	Helium
	Split ratio:	20/1
	Relative mass fraction	of the main component:
	Initial analysis:	Mean = 99.7%, s = 0.01% (7 sub samples in duplicate, November 2008)
	Re-analysis:	Mean = 99.7%, s = 0.03% (5 sub samples in duplicate, December 2011)
	Re-analysis:	Mean = 99.6%, s = 0.01% (5 sub samples in duplicate, November 2014)
	Re-analysis:	Mean = 99.6%, s = 0.02% (5 sub samples in duplicate, August 2017)
	Re-analysis:	Mean = $99.7\%$ , s = $0.01\%$ (5 sub samples in duplicate, June 2020)
Thermogravimetric analysis:		Volatile content < 0.1% and non volatile content < 0.2% mass fraction (November 2008)
Karl Fischer analysis:		Moisture content < 0.2% mass fraction (November 2008, December 2011 November 2014, August 2017, June 2020)

### Spectroscopic and other characterisation data

GC-MS:	Instrument: Column: Program: Injector: Transfer line temp: Carrier: Split ratio:	HP6890/5973 VF-1ms, 15 m x 0.25 mm l.D. x 0.25 μm 220 °C, 15 °C/min to 300 °C (5 min) 250 °C 280 °C Helium, 1.0 mL/min 20/1
	The retention time of the parent compound is reported along with the major peaks in the mass spectrum. The latter are reported as mass/charge ratios and (in brackets) as a percentage relative to the base peak.	
	Parent (7.7 min):	467 (M <sup>+</sup> , 8), 449 (17), 434 (27), 410 (29), 378 (100), 352 (12), 55 (54) <i>m/z</i>
TLC:	Conditions:	Kieselgel 60F <sub>254</sub> . Methanol/ethyl acetate (1:1)/1.5% ammonia solution Single spot observed, $R_f = 0.9$ . Visualization under UV at 254 nm.
IR:	Instrument: Range: Peaks:	Biorad WIN FTS3000MX FT-IR 4000-400 cm <sup>-1</sup> , KBr 3399, 2954, 2943, 1606, 1459, 1132, 1077, 1023, 957 cm <sup>-1</sup>
<sup>1</sup> H NMR:	Instrument: Field strength: Solvent: Spectral data:	Bruker AV400 400 MHz CDCl <sub>3</sub> (7.26 ppm) $\delta$ 0.11 (2H, dd, $J = 1.4$ , 4.8 Hz ), 0.43-0.53 (2H, m), 0.65-0.83 (2H, m), 1.04 (9H, s), 1.06-1.12 (1H, m), 1.30 (2H, dd, $J = 9.2$ , 13.1 Hz), 1.36 (3H, s), 1.64-1.88 (3H, m), 1.98 (1H, dt, $J = 5.6$ , 12.7 Hz), 2.12-2.38 (5H, m), 2.61 (1H, dd, $J = 5.1$ , 11.9 Hz), 2.89 (1H, m), 2.95-3.02 (2H, m), 3.53 (3H, s), 4.46 (1H, d, $J = 1.8$ Hz), 4.97 (1H, bs), 5.89 (1H, s), 6.51 (1H, d, $J = 8.0$ Hz), 6.68 (1H, d, $J = 8.0$ Hz) ppm
<sup>13</sup> C NMR:	Instrument: Field strength: Solvent: Spectral data:	Bruker AV400 151 MHz CDCl <sub>3</sub> (77.16 ppm) δ 3.2, 4.1, 9.5, 18.2, 20.1, 22.9, 26.4, 29.6, 33.4, 35.6, 36.0, 40.4, 43.70, 43.72, 46.5, 52.5, 58.3, 59.5, 79.5, 80.9, 97.1, 116.3, 119.6, 128.4, 132.6, 137.2, 145.4 ppm
Melting point:		213-217 °C
Microanalysis:	Found: Calculated:	C = 74.7 %, H = 9.1 %, N = 3.0 % (November 2008) C = 74.5 %, H = 8.8 %, N = 3.0 % (Calculated for $C_{29}H_{41}NO_4$ )