

Australian Government

Department of Industry, Science and Resources

National Measurement Institute



H .HCI

CERTIFIED REFERENCE MATERIAL CERTIFICATE OF ANALYSIS

NMIA D792f: (±)-3,4-Methylenedioxymethamphetamine hydrochloride

Report ID: D792f.2023.01 (Bottled 200707)

Chemical Formula: C₁₁H₁₅NO₂.HCl

Molecular Weight: 229.7 g/mol (HCl), 193.2 g/mol (base)

Certified value

Batch No.	CAS No.	Purity (mass fraction)
20-D-01	64057-70-1 (HCI) 42542-10-9 (base)	99.8 ± 0.3%

The uncertainty has been calculated according to ISO Guide 35 and is stated at the 95% confidence limit (k = 2).

IUPAC name: 1-(1,3-Benzodioxol-5-yl)-N-methyl-2-propanamine hydrochloride

Expiration of certification: The property values are valid till 29 June 2026, three years from the date of re-certification provided the **unopened** material is handled and stored in accordance with the recommendations below. The material as issued in the unopened container and stored as recommended below should be suitable for use beyond this date, subject to confirmation of batch stability from the issuing body. The expiry date/shelf life does not apply to sample bottles that have been opened. In such cases it is recommended that the end-user conduct their own in-house stability trials.

Description: White powder prepared by synthesis and certified for identity and purity by NMIA. Packaged in amber glass bottles with a septum and crimped aluminium cap or screw top cap.

Intended use: This certified reference material is suitable for use as a primary calibrator.

Instructions for use: Equilibrate the bottled material to room temperature before opening.

Recommended storage: When not in use this material should be stored at or below 25 °C in a closed container in a dry, dark area.

Metrological traceability: The certified purity value is traceable to the SI unit for mass (kg) through Australian national standards via balance calibration. In the mass balance approach all impurities are quantified as a mass fraction and subtracted from 100%. Quantitative NMR provides an independent direct measure of the mass fraction of the analyte of interest, calibrated with an internal standard certified for purity (mass fraction).

Stability: This material has demonstrated stability over a minimum period of three years. The measurement uncertainty at the 95% confidence interval includes a stability component which has been estimated from annual stability trials. The long-term stability of the compound in solution has not been examined.

Homogeneity assessment: The homogeneity of the material was assessed using purity assay by GC-FID on ten randomly selected 1-2 mg sub samples of the material. The material was judged to be sufficiently homogeneous at this level of sampling as the variation in analysis results between samples was not significantly different at a 95% confidence level from that observed on repeat analysis of the same sample.

Safety: Treat as a hazardous substance. Use appropriate work practices when handling to avoid skin or eye contact, ingestion or inhalation of dust. Refer to the provided safety data sheet.

Report ID: D792f.2023.01 (Bottled 200707) Product release date: 07 July 2020

S.R. Davies

Dr Stephen R. Davies, Team Leader, Chemical Reference Materials, NMI. 30 June 2023

This report supersedes any issued prior to 30 June 2023.

NATA Accreditation No. 198 / Corporate Site No. 14214.

CIPM MRA notice: This certificate is consistent with the capabilities that are included in Appendix C of the CIPM MRA drawn up by the CIPM. Under the CIPM MRA, all participating institutes recognize the validity of each other's calibration and measurement certificates for the quantities, ranges and measurement uncertainties specified in Appendix C. The "CIPM MRA Logo" and this statement attest only to the measurement(s) applied for determining the certified values on the certificate (for details see http://www.bipm.org).

Legal notice: Terms and Conditions associated with the provision of this reference material can be found on the NMIA website.

Characterisation Report:

The identity was confirmed by a range of spectroscopic techniques, NMR, IR and MS. The certified purity value was obtained by mass balance from a combination of traditional analytical techniques, including GC-FID, thermogravimetric analysis, Karl Fischer analysis and ¹H NMR spectroscopy. The purity value is calculated as per Equation 1.

Purity =
$$(100 \% - I_{ORG}) \times (100 \% - I_{VOL} - I_{NVR})$$

Equation 1

 I_{ORG} = Organic impurities of related structure, I_{VOL} = volatile impurities, I_{NVR} = non-volatile residue.

Supporting evidence is provided by qNMR and elemental microanalysis. The purity value by qNMR was obtained using the threeproton doublet at 1.29 ppm, the one-proton multiplet at 3.49 ppm, and the two-proton singlet at 5.97 ppm measured against a certified internal standard of sodium acetate.

GC-FID:	Instrument:	Agilent 7890
	Column:	HP-1, 30 m $ imes$ 0.32 mm l.D. $ imes$ 0.25 μ m
	Program:	120 °C (1 min), 10 °C/min to 220 °C, 20 °C/min to 300 °C (5 min)
	Injector:	250 °C
	Detector Temp:	320 °C
	Carrier:	Helium
	Split ratio:	20/1
	Relative mass fraction of the main component as the free base:	
	Initial analysis:	Mean = 100.0%, s = 0.04% (10 sub samples in duplicate, May 2020)
	Re-analysis:	Mean = 100.0 %, s = 0.002% (5 sub samples in duplicate, April 2021)
	Re-analysis:	Mean = 100.0 %, s = 0.0 % (5 sub samples in duplicate, June 2023)
Karl Fischer analysis:		Moisture content ≤ 0.1% mass fraction (May 2020 and June 2023)
		Moisture content 0.2% mass fraction (March 2021)
Thermogravimetric analysis:		
-	tric analysis:	Volatiles content < 0.1% and non-volatile residue < 0.2% mass fraction (May2020)
QNMR:	tric analysis: Instrument:	Volatiles content < 0.1% and non-volatile residue < 0.2% mass fraction (May2020) Bruker Avance-III-500
QNMR:		
QNMR:	Instrument:	Bruker Avance-III-500
QNMR:	Instrument: Field strength:	Bruker Avance-III-500 500 MHz
QNMR:	Instrument: Field strength: Solvent:	Bruker Avance-III-500 500 MHz D_2O (4.79 ppm)
QNMR:	Instrument: Field strength: Solvent: Internal standard:	Bruker Avance-III-500 500 MHz D_2O (4.79 ppm) Sodium acetate (60.1% mass fraction) Mean (1.29 ppm) = 100.1%, s = 0.1% (5 sub samples, May 2020) Mean (3.49 ppm) = 99.97%, s = 0.3% (5 sub samples, May 2020)
QNMR:	Instrument: Field strength: Solvent: Internal standard:	Bruker Avance-III-500 500 MHz D_2O (4.79 ppm) Sodium acetate (60.1% mass fraction)
QNMR:	Instrument: Field strength: Solvent: Internal standard: Initial analysis:	Bruker Avance-III-500 500 MHz D_2O (4.79 ppm) Sodium acetate (60.1% mass fraction) Mean (1.29 ppm) = 100.1%, s = 0.1% (5 sub samples, May 2020)

Spectroscopic and other characterisation data

GC-MS:		Agilent 6890/5973 DB-5MS, 30 m x 0.25 mm I.D. x 0.25 μ m 120 °C (1 min), 10 °C/min to 220 °C, 20 °C/min to 300 °C (3 min) 250 °C 20/1 280 °C Helium 50-550 <i>m/z</i> e free base is reported with the major peaks in the mass spectra. The latter are reported and (in brackets) as a percentage relative to the base peak.
	Parent (7.2 min):	136 (5), 135 (9), 105 (2), 77 (6), 58 (100), 56 (4), 51 (4) <i>m</i> / <i>z</i>
ESI-MS:	Instrument: Operation: Ionisation: EM voltage: Cone voltage: Peak:	Micromass Quatro LC Micro Positive ion mode, direct infusion at 10 μL/min ESI spray voltage at 2.5 kV positive ion 650 V 20 V 194.1 (M+H ⁺) <i>m/z</i>
TLC:	Conditions:	Kieselgel 60 F_{254} . TBME/Diethyl ether/triethylamine (45:45:10) Single spot observed, $R_f = 0.2$. Visualisation with UV at 254 nm.
IR:	Instrument: Range: Peaks:	Bruker Alpha Platinum ATR 4000-400 cm ⁻¹ , neat 2946, 2831, 2765, 2710, 2457, 1488, 1441, 1244, 1030, 930, 797 cm ⁻¹
¹ H NMR:	Instrument: Field strength: Solvent: Spectral data:	Bruker Avance III-500 500 MHz D_2O (4.79 ppm) δ 1.28 (3H, d, $J = 6.6$ Hz), 2.71 (3H, s), 2.84 (2H, dd, $J = 7.7$, 14.0 Hz), 3.05 (1H, dd, $J = 6.6$, 14.0 Hz), 3.49 (1H, m), 5.97 (2H, s), 6.79 (1H, dd, $J = 1.6$, 7.9 Hz), 6.85 (1H, d, $J = 1.6$ Hz), 6.89 (1H, d, $J = 8.0$ Hz) ppm Isopropanol estimated at 0.05% mass fraction was observed in the ¹ H NMR
¹³ C NMR:	Instrument: Field strength: Solvent: Spectral data:	Bruker Avance III-500 126 MHz D₂O δ 14.8, 29.9, 38.4, 56.5, 101.1, 108.7, 109.7, 122.8, 129.4, 146.3, 147.5 ppm
Melting point:		150-152 °C
Microanalysis:	Found: Calculated:	C = 57.6%; H = 7.0%; N = 6.0% (May 2020) C = 57.5%; H = 7.0%; N = 6.1% (Calculated for $C_{11}H_{15}NO_2.HCI$)