

# **Australian Government**

### **National Measurement Institute**



#### REFERENCE MATERIAL PRODUCT INFORMATION SHEET

**Report ID: D782b.2017.01 (Ampouled 090107)** 

This batch of ampoules was prepared from the bulk material on 7<sup>th</sup> January 2009.

Compound Name: d3-Nandrolone sulfate (triethylammonium salt)

Description: Off white solid

Collection Number: D782b Chemical Formula: C<sub>24</sub>H<sub>38</sub>D<sub>3</sub>NO<sub>5</sub>S

CAS Number: N/A

Structure:

Batch Number: 08-S-04 Molecular Weight: 458.7 Release date: December 2008

Synonyms:  $(16,16,17\alpha-d_3)$ -Nandrolone sulfate, triethylammonium salt

 $d_3$ -17 $\beta$ -sulfooxy-4-estren-3-one triethylammonium salt  $d_3$ -estr-4-en-17 $\beta$ -ol-3-one triethylammonium salt

The main component of this material is  $d_3$ -nandrolone sulfate as a combination of the triethylammonium salt (~78%) and as the protonated sulfate (~22%).  $d_2$ -,  $d_1$ - and  $d_0$ -Nandrolone sulfate are also present. The stated mass of the analyte per ampoule represents the combined masses of deuterated ( $d_3$ ,  $d_2$  and  $d_1$ ) and  $d_0$ - nandrolone sulfate anion in the material.

The compound is supplied as a dried aliquot in a sealed ampoule and is intended for a single use to prepare a standard solution containing D782b. Open the ampoule and carefully rinse the interior at least three times with a suitable organic solvent (e.g. methanol). This will transfer approximately 651  $\mu$ g of anhydrous nandrolone sulfate anion (d<sub>3</sub>, d<sub>2</sub>, d<sub>1</sub> and d<sub>0</sub>).

This material should be considered for use as an internal standard only.

Isotopic Purity:  $d_3 \approx 92\% \ \left[ = \frac{d_3}{d_3 + d_2 + d_1 + d_0} \ \times 100 \right]$ 

 $d_0 < 0.5\% \ [ = \frac{d_0}{d_3} \times 100]$ 

(determined by SIM analysis of d<sub>3</sub>-nandrolone used to prepare D782b)

HPLC: Instrument: Waters Model 1525 Binary pump, 717 plus autosampler

Column: Alltima C-18, 5  $\mu$ m (4.6 mm  $\times$  150 mm)

Mobile Phase: Acetonitrile/ MilliQwater

The aqueous phase was buffered at pH 4.2 using 10mM NH<sub>4</sub>OAc Gradient 0-5 min 75% A, 10-18 min 40% A, 20-26 min 75% A

Flow Rate: 1.0 mL/min

Detector: Waters PDA 2998 operating at 242 nm

Relative peak area response of main component:

Initial analysis: Mean = 95.97%, s = 0.18% (7 ampoules in duplicate, January 2009) Re-analysis: Mean = 90.1%, s = 0.5% (5 ampoules in duplicate, February 2012) Re-analysis: Mean = 84%, s = 0.9% (5 ampoules in duplicate, January 2015) Re-analysis: Mean = 81.4%, s = 1.0% (6 ampoules in duplicate, November 2017)

Accredited for compliance with ISO Guide 34.

105 Delhi Road North Ryde NSW 2113 Tel: +61 2 9449 0111 www.measurement.gov.au ABN: 74 599 608 295



# The following analytical data was obtained on the bulk material subsequently used in the preparation of the ampoules.

The purity value was obtained from traditional analytical techniques. The purity estimate by traditional analytical techniques was obtained by subtraction from 100 % of total impurities by HPLC with UV detection, thermogravimetric analysis, Karl Fischer analysis and <sup>1</sup>H NMR. Supporting evidence is provided by elemental microanalysis.

HPLC: Instrument: Waters Model 1525 Binary pump, 717 plus autosampler

Column: Alltima C-18, 5  $\mu$ m (4.6 mm  $\times$  150 mm)

Mobile Phase: Acetonitrile/MilliQ water

The aqueous phase was buffered at pH 4.2 using 10mM NH<sub>4</sub>OAc Gradient 0-5 min 75% A, 10-18 min 40% A, 20-26 min 75% A

Flow Rate: 1.0 mL/min

Detector: Waters PDA 996 at 254 nm Relative peak area response of main component:

Initial analysis: Mean = 96.6%, s = 0.06% (10 sub samples in duplicate, May 2008)

ESI-MS: Instrument: Micromass Quatro Micro

Operation: Negative ion mode, direct infusion at 5  $\mu$ L/min Ionisation: ESI spray voltage at 3.0 kV negative ion

EM voltage: 650 V Cone voltage: 30 V

Peak:  $356 \text{ (M-Et}_3\text{NH}^+\text{)} m/z$ 

TLC: Conditions: Kieselgel 60F<sub>254</sub>. Chloroform/methanol (17/3)

Single spot observed,  $R_f = 0.32$ . Visualisation with UV at 254 nm

IR: Biorad FTS300MX FT-IR

Range: 4000-400 cm<sup>-1</sup>, KBr pellet

Peaks: 3034, 2909, 2518, 2361, 1680, 1622, 1472, 1260, 1196, 602 cm<sup>-1</sup>

<sup>1</sup>H NMR: Instrument: DMX 600

Field strength: 600 MHz Solvent: CDCl<sub>3</sub>

Spectral data: δ 0.85 (3H, s), 0.8-0.9 (1H, m), 1.0-1.1 (2H, m), 1.2-1.4 (4H, m) 1.41 ("6.7"

H, t, J = 7.3 Hz), 1.51 (1H, m), 1.62 (1H, dd, J = 7.3, 12.3 Hz), 1.80 (2H, m), 1.97 (1H, m), 2.07 (1H, m), 2.2-2.3 (3H, m), 2.40 (1H, m), 2.48 (1H, dd, J =

1.5, 7.9 Hz), 3.05 ("4.7"H, t, J = 7.3 Hz) 5.83 (1H, s) ppm

<sup>13</sup>C NMR: Instrument: DMX 600

Field strength: 150 MHz Solvent: d<sub>4</sub>-MeOH (48.0 ppm)

Spectral data: 8 10.6, 11.1, 22.9, 26.1, 26.7, 30.9, 35.5, 36.3, 36.7, 40.4, 42.6, 42.7, 42.9,

49.5, 50.0, 123.8, 169.8, 201.9 ppm

Thermogravimetric analysis: Initial volatile content < 0.1% and non volatile residue < 0.2% mass fraction

(July 2008)

Karl Fischer analysis: Moisture content 0.3% mass fraction (February 2008)



#### **Expiration of certification**

The property values are valid till  $8^{th}$  November 2020, i.e. three years from the date of re-certification provided the **unopened** material is handled and stored in accordance with the recommendations below. The material as issued in the unopened container and stored as recommended below should be suitable for use beyond this date, subject to confirmation of batch stability from the issuing body.

The expiry date/shelf life does not apply to ampoules that have been opened. In such cases it is recommended that the end-user conduct their own in-house stability trials.

The long-term stability of the compound in solution has not been examined.

In the absence of stability data the measurement uncertainty at the 95% coverage interval has been expanded to accommodate any potential change in the property value. The stability component has been estimated from stability trials conducted on similar materials by NMI Australia over the last 10 years.

## **Recommended storage**

When not in use this material should be stored at or below 4 °C in a closed container in a dry, dark area.

#### Intended use

For *in vitro* laboratory analysis only.

#### Caution

Treat as hazardous substance. Use appropriate work practices when handling to avoid skin or eye contact, ingestion or inhalation of dust.

#### Legal notice

Neither NMI nor any person acting on NMI's behalf assumes any liability with respect to the use of, or for damages resulting from the use of, this reference material or the information contained in this certificate.

Authorised by:

S.R. Davies

Dr Stephen R. Davies, Team Leader,

Chemical Reference Materials, NMI.

Dated: 21 November, 2017.

Characterisation data and property values specified in this report supersede those in all reports issued prior to 21st November 2017.



Accredited for compliance with ISO Guide 34.
This document shall not be reproduced except in full
Accreditation Number: 198

Corporate Site Number: 14214